

**Catalog No. TGF4326A1BL****Description: SW FUSED GD 600A 3P 240V N1 BTM A****UPC No 783164644586****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. TH3225J

Descriptors

Category	General Duty
GO Schedule	SA

Specifications

Voltage	240 AC
Amperage	600 A
Poles	3
Wires	4
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Options	Bottom Feed
Wire Range (Cu/Al)	(1) 2-600 or (2) 1/0-250
240 Vac, NEC Std, 1-ph	75.0 hp
240 Vac, NEC Std, 3-ph	200.0 hp
480 Vac, NEC Std, 3-ph	400.0 hp
600 Vac, NEC Std, 3-ph	500.0 hp

Classifications

cUL Listed	Yes
UL Listed	Yes

Dimensions

Height	54.1 in
Depth	8.5 in
Width	22.9 in
Weight	117 lb

