

**Catalog No. THF3366A1VW****Description: SW FUSED HD 600A 3P 600V N1 VW A****UPC No 783164645415****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. TH3225J

**Descriptors**

|             |            |
|-------------|------------|
| Category    | Heavy Duty |
| GO Schedule | S1         |

**Specifications**

|                        |                 |
|------------------------|-----------------|
| Voltage                | 600 AC          |
| Amperage               | 600 A           |
| Poles                  | 3               |
| Fusing                 | Fusible         |
| Enclosure              | NEMA 1 (Indoor) |
| Options                | Window          |
| Wire Range (Cu/Al)     | (2) 4-600       |
| 240 Vac, NEC Std, 1-ph | 75.0 hp         |
| 240 Vac, NEC Std, 3-ph | 200.0 hp        |
| 480 Vac, NEC Std, 3-ph | 400.0 hp        |
| 600 Vac, NEC Std, 3-ph | 500.0 hp        |

**Classifications**

|            |     |
|------------|-----|
| cUL Listed | Yes |
| UL Listed  | Yes |

**Dimensions**

|        |         |
|--------|---------|
| Height | 54.1 in |
| Depth  | 8.5 in  |
| Width  | 24.5 in |
| Weight | 117 lb  |

  
**by ABB**

