

**Catalog No. THF3366ASVW****Description: SW FUSED HD 600A 3P 600V N4X VW A****UPC No 783164645439****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. TH3225J

Descriptors

Category	Heavy Duty
GO Schedule	S1

Specifications

Voltage	600 AC
Amperage	600 A
Poles	3
Fusing	Fusible
Enclosure	NEMA 4/4X Water/Dust-tight
Options	Window
Wire Range (Cu/Al)	(2) 4-600
240 Vac, NEC Std, 1-ph	75.0 hp
240 Vac, NEC Std, 3-ph	200.0 hp
480 Vac, NEC Std, 3-ph	400.0 hp
600 Vac, NEC Std, 3-ph	500.0 hp

Classifications

cUL Listed	Yes
UL Listed	Yes

Dimensions

Height	60.1 in
Depth	9.1 in
Width	26.7 in
Weight	184 lb


by ABB

