



Representative Image

Catalog No. RMS212240CHLBRB

Description: MTR STACK 2-400A 3PH1PH RNGL LVB +BRKRS

UPC No 783164684230

Home > Modular Metering > ReliaMod > ReliaMod Meter Module

Descriptors

Category	ReliaMod Meter Module
----------	-----------------------

Specifications

Enclosure	N3R Outdoor
Meter Equipment Group (MEG) Approved	Yes
Socket Amperage	400 A
Main Phase Input	3-Phase
Socket Phase Output	1-Phase
Voltage	120/240V
Socket Type	Ringless
No of Sockets	2
Socket Factory Installed Jaw Configuration	5-Jaw
Socket Bypass	Lever
Horizontal Bus Amperage	1200 A
Meter Module Tenant Breaker Provisions	Two 400A XT5N TMA 65 KAIC Tenant Breakers Included Factory Installed
Additional Notes	For tenant breaker load lugs, please refer to breaker specifications
Height (Inches)	70.3
Depth (Inches)	10.8
Width (Inches)	23.3
Estimated Weight (lbs)	263
Tenant Neutral Lugs (Per each socket) AWG/kcmil Al/Cu	(2) 2/0-500
Tenant Ground Lugs (Per each socket) AWG/kcmil Al/Cu	#6-300