

Catalog No. RMS28422LRLR

Description: MTR STACK 4-225A 3PH-1PH RINGLESS 10-22K

UPC No 783164683226

Home > Modular Metering > ReliaMod > ReliaMod Meter Module



Representative Image

Descriptors

Category	ReliaMod Meter Module
----------	-----------------------

Specifications

Enclosure	N3R Outdoor
Meter Equipment Group (MEG) Approved	Yes
Socket Amperage	225 A
Main Phase Input	3-Phase
Socket Phase Output	1-Phase
Voltage	120/240V
Socket Type	Ringless
No of Sockets	4
Socket Factory Installed Jaw Configuration	5-Jaw
Socket Bypass	None
Horizontal Bus Amperage	800 A
Meter Module Tenant Breaker Provisions	Only Accepts 10-22 KAIC Formula A1 & A2 Tenant Breakers
Additional Notes	For tenant breaker load lugs, please refer to breaker specifications
Height (Inches)	71.9
Depth (Inches)	9.6
Width (Inches)	18.4
Estimated Weight (lbs)	220
Tenant Neutral Lugs (Per each socket) AWG/kcmil Al/Cu	#6-300
Tenant Ground Lugs (Per each socket) AWG/kcmil Al/Cu	#14-2/0