



Representative Image

**Catalog No. RMS28512HRGR**

**Description: MTR STACK 5-125A 3PH1PH RING SKT 42-100K**

**UPC No 783164684032**

**Home > Modular Metering > ReliaMod > ReliaMod Meter Module**

Descriptors

|          |                       |
|----------|-----------------------|
| Category | ReliaMod Meter Module |
|----------|-----------------------|

Specifications

|                                                       |                                                                      |
|-------------------------------------------------------|----------------------------------------------------------------------|
| Enclosure                                             | N3R Outdoor                                                          |
| Socket Amperage                                       | 125 A                                                                |
| Main Phase Input                                      | 3-Phase                                                              |
| Socket Phase Output                                   | 1-Phase                                                              |
| Voltage                                               | 120/240V                                                             |
| Socket Type                                           | Ring Type                                                            |
| No of Sockets                                         | 5                                                                    |
| Socket Factory Installed Jaw Configuration            | 4-Jaw                                                                |
| Socket Bypass                                         | None                                                                 |
| Horizontal Bus Amperage                               | 800 A                                                                |
| Meter Module Tenant Breaker Provisions                | Only Accepts 42-100 KAIC TEY/TEYF/TEYL Tenant Breakers               |
| Additional Notes                                      | For tenant breaker load lugs, please refer to breaker specifications |
| Height (Inches)                                       | 63.2                                                                 |
| Depth (Inches)                                        | 9.5                                                                  |
| Width (Inches)                                        | 13.9                                                                 |
| Estimated Weight (lbs)                                | 155                                                                  |
| Tenant Neutral Lugs (Per each socket) AWG/kcmil Al/Cu | #14-2/0                                                              |
| Tenant Ground Lugs (Per each socket) AWG/kcmil Al/Cu  | #14-2/0                                                              |