


Type 4X Stainless Steel Two Door Floormount Enclosure *HN4 FM SS*

Series

Continuous Hinge Door with Handle



Application

- Designed to house electrical, electronic, hydraulic or pneumatic controls and instruments.
- Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem.

Construction

- Formed 12 gauge 304 or 316 stainless steel.
- Smooth, continuously welded seams without knockouts, cutouts or holes.
- Heavy duty stainless steel lifting eyebolts are provided with reinforcing support angles.
- Doors are supported with heavy gauge continuous hinges.
- New 3-pt padlocking door handle.
- Seamless poured-in place gasket.
- A grounding stud is provided in the enclosure and a bonding stud is provided on the door.
- Center post is removable for easy installation of the inner panel.
- 12" floor stands are welded to the enclosure.

Standards

- UL 508A Type 3R, 4X and 12
- CSA Type 3R, 4X and 12
- Complies with:
 - NEMA Type 3R, 4X, 12 and 13
 - IEC 60529, IP66

Finish

- Cover and enclosure are natural stainless steel with a smooth brushed finish.
- Removable 10 gauge inner panel is finished in white powder coating.

Accessories

- Additional Inner Panels
- Barrier Kits for Type 4 Floormount
- Drip Shield Kit
- Window Kits
- Lighting
- Door Stop Kit
- Mechanical Interlock
- Type 12/4, 4X Handle Kits
- Climate Control
- General Accessories

New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

304 S.S. Part Number	316 S.S. Part Number	H	Enclosure W	D	Panel H	W
HN4FM604812SS	HN4FM604812S1 6	60.13	48.06	12.69	56.00	44.00
HN4FM604818SS	HN4FM604818S1 6	60.13	48.06	18.69	56.00	44.00
HN4FM606012SS	HN4FM606012S1 6	60.13	60.06	12.69	56.00	56.00
HN4FM606018SS	HN4FM606018S1 6	60.13	60.06	18.69	56.00	56.00
HN4FM726012SS	HN4FM726012S1 6	72.13	60.06	12.69	68.00	56.00
HN4FM726018SS	HN4FM726018S1 6	72.13	60.06	18.69	68.00	56.00
HN4FM727212SS	HN4FM727212S1 6	72.13	72.06	12.69	68.00	68.00
HN4FM727218SS	HN4FM727218S1 6	72.13	72.06	18.69	68.00	68.00
HN4FM727224SS	HN4FM727224S1 6	72.13	72.06	24.69	68.00	68.00

Tags: **HN4FM, floormount, two door, stainless steel, Type 4X, NEMA 4X, instrument, hydraulic, pneumatic, 304, 316, continuous hinge, handle**

Data subject to change without notice.