

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	04JAN2022	RG	CW

- NOTES:
1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PA
RATED VOLTAGE: 50V
RATED CURRENT: 6.5A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 0.8KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 100 CYCLES
OPERATION TEMPERATURE: -30~+90°C
WIRE RANGE: 0.08~0.52 mm² (28~20 AWG)
CONTACT TYPE: CRIMP CONTACT
2. CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No.REFER TO DRAWING:T20700X20XX000)

- 注释:
1. 技术参数:
绝缘材料: PA
额定电压: 50V
额定电流: 6.5A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 0.8KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 100次
工作温度: -30~+90°C
接线范围: 0.08~0.52 mm² (28~20 AWG)
接线类型: 冷压接
2. 端子需要单独订购.
(订货号参考图面: T20700X20XX000)

T2010124201-000	H1A-012-F	H1A-012 FEMALE INSERT H1A-012 母插
PART NUMBER 产品料号	PART DESCRIPTION 产品描述	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN ROBERT GAN 20SEP2021	TE TE Connectivity		
		CHK GINO YAO 20SEP2021			
		APVD CHRIS WANG 20SEP2021			
		PRODUCT SPEC 108-137574			
		APPLICATION SPEC 114-137574	NAME H1A-012-F		
		WEIGHT	SIZE A3	CAGE CODE 00779	DRAWING NO T2010124201000
		CUSTOMER DRAWING	SCALE 2:1	SHEET 1 OF 1	REV A

DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
		0 PLC	±
		1 PLC	±
		2 PLC	±
		3 PLC	±
		4 PLC	±
		ANGLES	±
MATERIAL		FINISH	

