

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	18MAR2015	DW	CW
	B	ECR-15-018270	07DEC2015	DW	CW
	C	ECR-21-111798	23SEP2021	WQR	CW
	D	ECR-25-237961	17MAR2025	ABS	RB

NOTES:

1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 1000V
RATED CURRENT: 100A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 8KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
OPERATION TEMPERATURE: $-40^{\circ}C \sim +125^{\circ}C$
WIRE RANGE: $10.0mm^2 \sim 35.0mm^2$
CONTACT TYPE: CRIMP CONTACT

2. CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING:T20500010XX000)

注释:

1. 技术参数:
绝缘材料: PC
额定电压: 1000V
额定电流: 100A
绝缘电阻: $\geq 400M\Omega$
脉冲电压: 8KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40^{\circ}C \sim +125^{\circ}C$
接线范围: $10.0mm^2 \sim 35.0mm^2$
接线类型: 冷压接

2. 端子需要单独订购.
(订货号参考图面: T20500010XX000)

HMN-D2-MC	T2111028101-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	18MAR2015	TE Connectivity		
		CHK	18MAR2015			
		APVD	18MAR2015			
		PRODUCT SPEC				
			108-137058	NAME HMN-D2-MC		
		APPLICATION SPEC				
			114-137058	SIZE	CAGE CODE	DRAWING NO
		MATERIAL	-	A300779		©-T2111028101000
		FINISH	-	SCALE		1:1
			-	SHEET		1 OF 1
			-	REV		D
			-	CUSTOMER DRAWING		

