

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	ECR-15-018270	09DEC2015	DW	CW
	B1	ECR-16-006849	13MAY2016	RL	CW
	C	ECR-21-111798	28SEP2021	WQR	CW
	D	ECR-25-237961	12JUN2025	ABS	RB

- NOTES:
- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 250V
RATED CURRENT: 10A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 4KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
OPERATION TEMPERATURE: $-40\sim+125^{\circ}C$
WIRE RANGE: $0.14\sim 2.5\text{ mm}^2$ (26~14 AWG)
CONTACT TYPE: CRIMP CONTACT
 - CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20200X20XX000)

- 注释:
- 技术参数:
绝缘材料: PC
额定电压: 250V
额定电流: 10A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 4KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40\sim+125^{\circ}C$
接线范围: $0.14\sim 2.5\text{ mm}^2$ (26~14 AWG)
接线类型: 冷压接
 - 端子需要单独订购.
(订货号参考图面: T20200X20XX000)

T2111122201-001	HMN-012-F WITHOUT LOGO HMN-012模块母插 不带LOGO, 产品型号和认证标示
T2111122201-000	HMN-012-F WITH LOGO HMN-012模块母插
PART NUMBER 料号	PART DESCRIPTION 描述

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 14APR2015 David Wang	 TE Connectivity		
		CHK 14APR2015 Chris.Wang			
		APVD 14APR2015 Xiang.Xu			
		PRODUCT SPEC 108-137121			
		APPLICATION SPEC 114-137121	NAME HMN-012-F		
		WEIGHT -	SIZE A3	CAGE CODE 00779	DRAWING NO T2111122201000
		CUSTOMER DRAWING	SCALE 1:1	SHEET 1 OF 1	RESTRICTED TO REV D

DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
		0 PLC 1 PLC 2 PLC 3 PLC 4 PLC ANGLES	± ± ± ± ± ±
MATERIAL -		FINISH -	-

T2111122201-001 SHOWN, ALL DIMENSIONS ARE SAME AS T2111122201-000, EXCEPT WITHOUT LOGO, TYPE DESCRIPTION, TUV AND CUL MARK
不带 LOGO, 产品型号和认证标示

T2111122201-000 SHOWN,
带 LOGO, 产品型号, 认证标示

