

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	16APR2015	DW	CW
	B	ECR-15-018270	09DEC2015	DW	CW
	C	ECR-21-111798	27SEP2021	WQR	CW
	D	ECR-25-237961	13JUN2025	ABS	RB

- NOTES:
1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 830V
RATED CURRENT: 16A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 8KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
OPERATION TEMPERATURE: $-40\sim+125^{\circ}C$
WIRE RANGE: $0.14\sim 4\text{ mm}^2$ (26~12 AWG)
CONTACT TYPE: CRIMP CONTACT
 2. CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING:T20300X20XX000)

- 注释:
1. 技术参数:
绝缘材料: PC
额定电压: 830V
额定电流: 16A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 8KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40\sim+125^{\circ}C$
接线范围: $0.14\sim 4\text{ mm}^2$ (26~12 AWG)
接线类型: 冷压接
 2. 端子需要单独订购.
(订货号参考图面: T20300X20XX000)

HMN-006-PF	T2111063201-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 16APR2015 David Wang	TE Connectivity HMN-006-PF		
		CHK 16APR2015 Chris.Wang			
		APVD 16APR2015 Xiang.Xu			
		PRODUCT SPEC 108-137120			
		APPLICATION SPEC 114-137120	SIZE CAGE CODE DRAWING NO RESTRICTED TO A300779C-T2111063201000 -		
		WEIGHT -			
CUSTOMER DRAWING		SCALE 3:2		SHEET 1 OF 1	REV D

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
mm			
	0 PLC	±0	
	1 PLC	±0	
	2 PLC	±0	
	3 PLC	±0	
	4 PLC	±0	
	ANGLES	±0	
MATERIAL		FINISH	
-		-	
-		-	

