


REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	29APR2015	DW	CW
	B	ECR-15-018270	09DEC2015	DW	CW
	C	ECR-21-111798	27SEP2021	WQR	CW
	D	ECR-25-237961	11JUN2025	ABS	RB

NOTES:
1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 400V
RATED CURRENT: 16A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 6KV
POLLUTION DEGREE: 3
CONTACT RESISTANCE: $\leq 5m\Omega$
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
OPERATION TEMPERATURE: $-40^{\circ}C\sim +125^{\circ}C$
WIRE RANGE: 0.5~2.5mm²
CONTACT TYPE: SPRING TYPE.

注释:
1. 技术参数:
绝缘材料: PC
额定电压: 400V
额定电流: 16A
绝缘电阻: $\geq 400M\Omega$
脉冲电压: 6KV
污染等级: 3
接触电阻: $\leq 5m\Omega$
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40^{\circ}C\sim +125^{\circ}C$
接线范围: 0.5~2.5mm²
接线类型: 弹片连接

HMN-005-FS	T2110052201-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN David Wang 29APR2015	TE Connectivity					
		CHK Chris. Wang 29APR2015						
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD Xiang Xu 29APR2015	NAME HMN-005-FS					
	0 PLC ±-	PRODUCT SPEC	SIZE CAGE CODE DRAWING NO RESTRICTED TO					
	1 PLC ±-	108-137119						
	2 PLC ±-	APPLICATION SPEC						
3 PLC ±-	4 PLC ±-	114-137119						
4 PLC ±-	ANGLES ±-	WEIGHT -	A300779C-T2110052201000					
MATERIAL - -	FINISH - -	CUSTOMER DRAWING		SCALE 3:2	SHEET 1 OF 1	REV D		