






P	LTR	DESCRIPTION	DATE	DWN	APVD
	B1	ECR-15-017530	02DEC2015	GY	CW
	B2	ECR-16-015492	08NOV2016	QY	CW
	C	ECR-21-105750	30JUN2021	BS	CW
	D	ECR-25-246911	26JUN2025	ABS	RB

- NOTES:
1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 250 V
RATED CURRENT: 10 A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 4 KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: 0.14-2.5 mm² (26-14 AWG)
CONTACT TYPE: CRIMP CONTACT
 2. CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING:T20200X10XX000)


- 注释:
1. 技术参数:
绝缘材料: PC
额定电压: 250V
额定电流: 10A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 4 KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
接线范围: 0.14-2.5 mm² (26-14 AWG)
接线类型: 冷压接
 2. 端子需要单独订购.
(订货号参考图面: T20200X10XX000)



M4 SCREW RECOMMENDED
TIGHTENING TORQUE 1.2Nm
M4 螺丝, 推荐锁紧力矩 1.2Nm




4X M3 SCREW RECOMMENDED
TIGHTENING TORQUE 0.5Nm
4X M3螺丝, 推荐锁紧力矩 0.5Nm



PANEL CUT OUT FOR INSERTS FOR USE
WITHOUT HOODS/HOUSINGS
不用防护外壳时芯件的安装开孔图

TYPE-1,T2020402101-000,TE LOGO
类型-1,T2020402101-000,TE LOGO

TYPE-2,T2020402101-001,STAINLESS STEEL SCREW,TE LOGO
类型-2,T2020402101-001,不锈钢螺丝,TE LOGO





THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 16DEC2014 RAGHAVENDRA H M	 TE Connectivity		
		CHK 16DEC2014 CHRIS WANG			
DIMENSIONS: mm		APVD 16DEC2014 XU XIANG	NAME HD-040-M		
		PRODUCT SPEC 108-137042	SIZE A3		
		APPLICATION SPEC 114-137042			
MATERIAL -		WEIGHT -	CAGE CODE 00779		
		CUSTOMER DRAWING	DRAWING NO T2020402101000		
		SCALE 1:1	SHEET 1 OF 2		REV D

REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
	-	SEE SHEET 1	-	-	-

NOTE:
SEE SHEET 1

注释:
见页 1




TYPE-3, T2020402101-002, STAINLESS STEEL SCREW, NO LOGO
类型-3, T2020402101-002, 不锈钢螺丝, 无LOGO



ALL DIMENSIONS ARE SAME AS TYPE 1,
EXCEPT THOSE DEFINED IN THIS TYPE.
除了在本类型中定义的尺寸外, 其它尺寸同类型 1

T2020402101-002	HD-040-M	HD-040 MALE INSERT, STAINLESS STEEL SCREW, NO LOGO HD-040 公插, 不锈钢螺丝, 无LOGO	TYPE-3 类 型-3
T2020402101-001	HD-040-M	HD-040 MALE INSERT, STAINLESS STEEL SCREW HD-040 公插, 不锈钢螺丝	TYPE-2 类 型-2
T2020402101-000	HD-040-M	HD-040 MALE INSERT HD-040 公插	TYPE-1 类 型-1
PART NUMBER 料 号	PART DESCRIPTION 描 述		TYPE 类 型

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 16DEC2014 RAGHAVENDRA H M	 TE Connectivity		
		CHK 16DEC2014 CHRIS WANG			
DIMENSIONS: mm		APVD 16DEC2014 XU XIANG	NAME HD-040-M		
		PRODUCT SPEC 108-137042			
		APPLICATION SPEC 114-137042	SIZE A3		
MATERIAL -		WEIGHT -			
			CAGE CODE 00779	DRAWING NO T2020402101000	RESTRICTED TO -
			CUSTOMER DRAWING		SCALE 1:1
				SHEET 2 OF 2	REV D