

REVISIONS


P	LTR	DESCRIPTION	DATE	DWN	APVD
	B2	ECR-19-000492	23JAN2019	AL	CW
	C	ECR-19-004179	24APR2019	AL	CW
	D	ECR-21-111798	27SEP2021	WQR	CW
	E	ECR-25-237961	13JUN2025	ABS	RB

- NOTES:
1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 50V
RATED CURRENT: 5A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 0.8KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: 0.08~0.52 mm² (28~20 AWG)
CONTACT TYPE: CRIMP CONTACT
 2. CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING:T20700X20XX000)

- 注释:
1. 技术参数:
绝缘材料: PC
额定电压: 50V
额定电流: 5A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 0.8KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
接线范围: 0.08~0.52 mm² (28~20 AWG)
接线类型: 冷压接
 2. 端子需要单独订购.
(订货号参考图面: T20700X20XX000)

T2111092201-000	HMN-009-F	HMN-009 FEMALE MODULE INSERT HMN-009模块母插
PART NUMBER 料 号	DESCRIPTION 描 述	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 24MAR2015 David Wang	 TE Connectivity			
		CHK 24MAR2015 Chris.Wang				
		APVD 24MAR2015 Xiang Xu	NAME HMN-009-F			
		PRODUCT SPEC 108-137064				
		APPLICATION SPEC 114-137064				
		WEIGHT -	SIZE A3	CAGE CODE 00779	DRAWING NO C-T2111092201000	RESTRICTED TO -
CUSTOMER DRAWING		SCALE 3:2	SHEET 1	OF 1	REV E	

DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
		0 PLC	±-
		1 PLC	±-
		2 PLC	±-
		3 PLC	±-
		4 PLC	±-
		ANGLES	±-
MATERIAL -		FINISH -	

