© 2026 TE Connectivity. All Rights Reserved.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	24SEP2015	DW	CW
	A1	ECR-17-014105	07OCT2017	YC	CW
	A2	ECR-19-004297	21MAR2019	SR	CW
	A3	ECR-26-269020	07MAY2026	RK	SC









AG	WIRE RANG (mm)	GL	GL (Lengthen)	H	SW2	SW1	PART DESCRIPTION 描 述	PART NUMBER 料 号	
M32x1.5	21-22.5	8	-	28.5	40	40	DLX-32-MEZ	嵌入式金属接头 (M32*1.5)(21-22.5)	T3709320122-000	OBSOLETE
M32x1.5	17-21	8	-	28.5	40	40	DLX-32-MET	嵌入式金属接头 (M32*1.5)(17-21)	T3709320112-000	
M32x1.5	22.5-25	8	-	28.5	40	40	DLX-32-ME	嵌入式金属接头 (M32*1.5)(22.5-25)	T3709320102-000	
M25x1.5	16-17.5	7	-	23.5	30	30	DLX-25-MEZ	嵌入式金属接头 (M25*1.5)(16-17.5)	T3709250122-000	
M25x1.5	13.5-16	7	-	23.5	30	30	DLX-25-MET	嵌入式金属接头 (M25*1.5)(13.5-16)	T3709250112-000	
M25x1.5	17.5-19	7	-	23.5	30	30	DLX-25-ME	嵌入式金属接头 (M25*1.5)(17.5-19)	T3709250102-000	
M25x1.5	19-21	7	-	23.5	30	30	DLX-25-MEC	嵌入式金属接头 (M25*1.5)(19-21)	T3709250142-000	
M24x1.5	10-14	7	-	23.5	30	30	DLX-24-MET	嵌入式金属接头 (M24*1.5)(10-14)	T3709240112-000	
M20x1.5	13.5-15	-	16	21.5	22	24	DLX-20-LME	嵌入式金属加长螺纹接头 (M20*1.5)(13.5-15)	T3709200202-000	
M20x1.5	11-13.5	6	-	21.5	22	22	DLX-20-MEZ	嵌入式金属接头 (M20*1.5)(11-13.5)	T3709200122-000	OBSOLETE
M20x1.5	8.5-11	6	-	21.5	22	22	DLX-20-MET	嵌入式金属接头 (M20*1.5)(8.5-11)	T3709200112-000	
M20x1.5	13.5-15	6	-	21.5	22	22	DLX-20-ME	嵌入式金属接头 (M20*1.5)(13.5-15)	T3709200102-000	
M16x1.5	8-9.5	-	10	19.5	17	18	DLX-16-MEZ	嵌入式金属加长螺纹接头 (M16*1.5)(8-9.5)	T3709161122-000	OBSOLETE
M16x1.5	8-9.5	6	-	19.5	17	18	DLX-16-MEZ	嵌入式金属接头 (M16*1.5)(8-9.5)	T3709160122-000	
M16x1.5	6.5-9	6	-	19.5	17	18	DLX-16-MET	嵌入式金属接头 (M16*1.5)(6.5-9)	T3709160112-000	OBSOLETE
M16x1.5	9.5-10.5	6	-	19.5	17	18	DLX-16-ME	嵌入式金属接头 (M16*1.5)(9.5-10.5)	T3709160102-000	
1/2-20UNF	3.5-5	4.8	-	17.5	13.9	13.9	DLX-1/2-20-UNF	嵌入式金属接头 (1/2-20UNF)(3.5-5)	T3709121131-000	
PG29	21-22.5	8	-	28.5	40	40	DLX-29-MSEZ	嵌入式金属接头 PG29 (21-22.5)	T3709290121-000	OBSOLETE
PG29	17.5-21	8	-	28.5	40	40	DLX-29-MSET	嵌入式金属接头 PG29 (17.5-21)	T3709290111-000	
PG29	22.5-25	8	-	28.5	40	40	DLX-29-MSE	嵌入式金属接头 PG29 (22.5-25)	T3709290101-000	
PG21	16-17.5	7	-	23.5	30	30	DLX-21-MSEZ	嵌入式金属接头 PG21 (16-17.5)	T3709210121-000	
PG21	13.5-16	7	-	23.5	30	30	DLX-21-MSET	嵌入式金属接头 PG21 (13.5-16)	T3709210111-000	
PG21	17.5-19	7	-	23.5	30	30	DLX-21-MSE	嵌入式金属接头 PG21 (17.5-19)	T3709210101-000	OBSOLETE
PG16	12-14	6	-	20.5	24	24	DLX-16-MSEZ	嵌入式金属接头 PG16 (12-14)	T3709160121-000	
PG16	9-12	6	-	20.5	24	24	DLX-16-MSET	嵌入式金属接头 PG16 (9-12)	T3709160111-000	
PG16	14-16	6	-	20.5	24	24	DLX-16-MSE	嵌入式金属接头 PG16 (14-16)	T3709160101-000	
PG13.5	11-13.5	6	-	21.8	22	22	DLX-13-MSEZ	嵌入式金属接头 PG13.5 (11-13.5)	T3709130121-000	
PG13.5	8.5-11	6	-	21.8	22	22	DLX-13-MSET	嵌入式金属接头 PG13.5 (8.5-11)	T3709130111-000	
PG13.5	13.5-15	6	-	21.8	22	22	DLX-13-MSE	嵌入式金属接头 PG13.5 (13.5-15)	T3709130101-000	
PG11	8.5-11	7.3	-	20	20	20	DLX-11-MSEZ	嵌入式金属接头 PG11 (8.5-11)	T3709110121-000	
PG11	6-8.5	7.3	-	20	20	20	DLX-11-MSET	嵌入式金属接头 PG11 (6-8.5)	T3709110111-000	OBSOLETE
PG11	11-13.5	7.3	-	20	20	20	DLX-11-MSE	嵌入式金属接头 PG11 (11-13.5)	T3709110101-000	
PG9	3.5-6	6	-	19.5	17	18	DLX-9-MSET	嵌入式金属接头 PG9 (3.5-6)	T3709090111-000	
PG9	6.5-9	6	-	19.5	17	18	DLX-9-MSE	嵌入式金属接头 PG9 (6.5-9)	T3709090101-000	

NOTES:

1. TECHNICAL CHARACTERISTICS:
   SHELL MATERIAL : BRASS,NICKEL-PLATED
   O RING: ELASTIC RUBBER
   SEAL MATERIAL: ELASTIC RUBBER
   OPERATION TEMPERATURE: -40°C-+100°C
   PROTECTION DEGREE: IP65
   WIRE RANGE: SEE TABLE

注释：

1. 技术参数：
   主体材料： 铜镀镍
   O 型圈： 弹性橡胶
   密封材料： 弹性橡胶
   工作温度： -40°C-+100°C
   防护等级： IP65
   夹线范围： 见表格

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±-
2 PLC ±-
3 PLC ±-
4 PLC ±-
ANGLES ±-

MATERIAL -
-

FINISH -
-

DWN DAVID WANG 24SEP2015
CHK CHRIS WANG 24SEP2015
APVD XIANG XU 24SEP2015
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

TE Connectivity

NAME METAL CABLE GLAND
BRASS NICKEL-PLATED
SPECIAL SEALING, IP65

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C-T3709XXXXXX000	-

CUSTOMER DRAWING | SCALE 4:1 | SHEET 1 OF 1 | REV A3