


NOTES:


1. INDICATOR IS FLUSH WITH SURFACE A BEFORE FUSE OPENS
INDICATOR EXTENDS .44 IN. [11.2mm] AFTER FUSE OPENS AND EXERTS
1 LBF AT THE END OF TRAVEL

REV.	DATE	ECO	DESCRIPTION	BY	CK	APP
A	4/27/2022	16903	INITIAL RELEASE	KMH	N/A	SEE ECO



OUTLINE DIMENSIONS
NOT TO BE USED FOR PRODUCTION

DIMENSIONS IN []
ARE MILLIMETERS

Approval stage / Etat d'approbation: APPROUVÉ POUR FABRICATION / APPROVED FOR MANUFACTURING	Product Class:/ Product Type:	E-RATED BOLT-IN AMP-TRAP	
	Product amp rating:/ Voltage rating:	100E 15.5kV	
Initial ECO / ECO initiale: ECO-16903-000		Title / Titre: A155B1D0R0-100E MEDIUM VOLTAGE	Weight : 2772 Masse :
Draw by / Dessiné par: Alma Balcazar	Date : 9/7/2022	Drawing / de dessin: OUT-1202798	
Checked by / Vérifié par: Yadyra Fang	Date : 9/7/2022		
Electrical Power 374 MERRIMAC STREET NEWBURYPORT,MA 01950		Éch / Scale : 1:2 Format / Size : B	Part / Article: SEE TABLE
		Page : 1/1	MERSEN
Ce plan strictement confidentiel est la propriété exclusive de la société MERSEN sans l'autorisation écrite de laquelle il ne peut être ni reproduit, ni copié, ni communiqué à des tiers. This drawing and specifications there on is property of MERSEN and shall not be reproduced or copied or used in whole or in part as the base for manufacture or sale of item without written permission.			

A155B1D0R0-100E
CATALOG NUMBER