



NSI INDUSTRIES PART NUMBER			BUNDLE DIAMETER		A IN (mm) +/- .250 (6.350mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .010 (.254mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .020 (.508mm)	F IN (mm) +/- .030 (.762mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING
			MIN IN (mm)	MAX IN (mm)									
5400-IR			.0625 (1.587mm)	1.437 (36.423mm)	5.840 (148.336mm)	.049 (1.244mm)	.140 (3.556mm)	.240 (6.096mm)	.175 (4.445mm)	.250 (6.350mm)	40 (178)	HB	N/A
7500-IR			.062 (1.57mm)	1.875 (47.625mm)	7.562 (192.075mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50(222)	HB	N/A
11500-IR			.062 (1.57mm)	3.062 (77.775mm)	11.250 (285.751mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	HB	N/A
14500-IR			.062 (1.57mm)	4.000 (101.600mm)	14.35 (364.49mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	HB	N/A
81200-IR			.187 (4.75mm)	2.06 (52.3mm)	8.700 (220.980mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	HB	N/A
141200-IR			.187 (4.75mm)	4.0625 (103.187mm)	15.093 (383.362mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120(534)	HB	N/A
								HIGH TEMP, UV & IMPACT RESISTANT STANDARD CABLE TIES					
					COLOR DESIGNATIONS: IT-30 = HIGH TEMP, IMPACT RESISTANT, UV BLACK HEAT STABILIZED					MATERIAL: NYLON 6/6 POLYAMIDE			

CONFIDENTIAL PROPERTY OF NSI INDUSTRIES, LLC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF NSI INDUSTRIES, LLC.