



Aluminum

Images

[Download Photo Image](#)[Download Dimensional Image](#)

Dimension A in Inches: .250-.350

Dimension B in Inches: .687

Dimension C in Inches: 1.210

Dimension D in Inches: 1.220

Dimension E in Inches: 1-5/16

Dimension F in Inches: 13/16

Application

These watertight fittings are designed for both indoor and outdoor applications. All fittings can be used in chemical and treatment plants as well as for offshore applications. Straight connector for use with portable cord provides liquid tight and water tight protection. Typical applications include wiring of motors, transformers, advanced machinery, refrigeration, and tools.

Product Information

Material: Aluminum

Certifications & Codes:

NEMA Standard: FB-1

UL File Number: E11259

UL Standard: UL514B

UNSPSC: 39121431

Catalog ID: CGA771350**UPC Number:** 78174787712**Description:** Connector, cord grip, straight, aluminum, k.o. size 3/4", cord range .250-.350

Application: These watertight fittings are designed for both indoor and outdoor applications. All fittings can be used in chemical and treatment plants as well as for offshore applications. Straight connector for use with portable cord provides liquid tight and water tight protection. Typical applications include wiring of motors, transformers, advanced machinery, refrigeration, and tools.

Trade Size: 3/4"**Country of Manufacture:** USA**Std Pkg Qty:** 100**Unit Qty:** 10