



US Steel

Images

[Download Photo Image](#)[Download Dimensional Image](#)

Dimension A in Inches: .850-.950

Dimension B in Inches: 1.187

Dimension C in Inches: 1.730

Dimension D in Inches: 1.900

Dimension E in Inches: 1 15/16

Dimension F in Inches: 1 1/4

Application

These watertight fittings, are designed for both indoor and outdoor applications. All fittings can be used in chemical and treatment plants as well as for offshore applications. Straight connector for use with portable cord provides liquid tight and water tight protection. Typical applications include wiring of motors, transformers, advanced machinery, refrigeration, and tools.

Product Information

Material: Steel

Finish: Zinc Electro-Plated

Certifications & Codes:

NEMA Standard: FB-1

UL File Number: E11259, cULus

UL Standard: UL514B

UNSPSC: 39121431

Catalog ID: CG773-950**UPC Number:** 78174727732**Description:** Connector, cord grip, straight, steel, k.o. size 1 1/4", cord range, .850-.950

Application: These watertight fittings, are designed for both indoor and outdoor applications. All fittings can be used in chemical and treatment plants as well as for offshore applications. Straight connector for use with portable cord provides liquid tight and water tight protection. Typical applications include wiring of motors, transformers, advanced machinery, refrigeration, and tools.

Trade Size: 1 1/4**Country of Manufacture:** USA**Std Pkg Qty:** 25**Unit Qty:** 5