

Hardware and Rough-In Products

Anchors — Non-Metallic (continued)

Hexagon Nuts

- For use with machine bolts
- Finest quality steel, zinc plated



CAT. NO.	SIZE	STD. CTN.
55-004P	6-32	1,000
55-005P	8-32	1,000
55-008P	1/4-20	1,000
55-010	5/16-18	1,000
55-012	3/8-16	1,000

Red-Cap® Anchor Kits

- Red Cap® anchors, screws and drill bit in reusable plastic kit box



CAT. NO.	DESCRIPTION	STD. CTN.
51-208	(100) #8 Anchors (100) 6 x 1" Panhead Screws (1) 3/16" Carbide-Tip Drill Bit	12
51-212*	(100) #12 Anchors (100) 10 x 1" Combination Slot/Phillips Head Screws (1) 1/4" Carbide-Tip Drill Bit	12
51-212HX	(100) #12 Anchors (100) 10 x 1" Hex-Slotted Screws (10) 1/4" Carbide-Tip Drill Bit	12
51-216	(50) #16 Anchors (50) 14 x 1 1/4" Panhead Screws	12

* Now with combination Slot/Phillips screws.

Self-Drilling Screws

- Drill their own hole and form mating threads
- #8 screws fasten combined material thickness up to 3/32"
- #10 screws fasten combined material thickness up to 1/4"
- Hex Washer Head (no slot)
- 1/4" hex head fits 54-090 Magnetic Driver
- 5/16" hex head fits 54-091 Magnetic Driver



CAT. NO.	SIZE	HEAD SIZE (IN.)	POINT NO.	STD. CTN.
54-301	8 x 3/4"	1/4	2	1,000
54-302P	10 x 5/8"	5/16	3	1,000
54-303P	10 x 1"	5/16	3	1,000
54-304	12-14 x 3/4"	5/16	3	1,000

Magnetic Drivers


- For driving self-piercing and self-drilling hex head screws
- Fits power screwdriver and electric drill chucks
- Strong permanent magnet holds screw in position



CAT. NO.	SIZE	STD. CTN.
54-091	5/16" x 1 1/2" Hex-Head Magnetic Driver	12
54-090	1/4" x 1 1/2" Hex-Head Magnetic Driver	12

Machine Bolts

- Steel, zinc plated
- Accurate, uniform threads
- Round heads standard; flat heads available in some sizes



CAT. NO.	SIZE	STD. CTN.
54-541P	8-32 x 1 1/2"	1,000
54-543P	8-32 x 1"	1,000
54-545P	8-32 x 1 1/2"	1,000
54-546P	8-32 x 2"	1,000
54-570P	1/4-20 x 3/8"	1,000
54-571P	1/4-20 x 1/2"	1,000
54-572P	1/4-20 x 3/4"	500
54-573P	1/4-20 x 1"	500

Red-Cap® Screw Anchors

- Superior holding power in solid masonry or concrete block



CAT. NO.	SIZE	FOR TAPPING SCREWS		DRILL* HOLE (IN.)	STD. CTN.
		SIZE	LENGTH (IN.)		
50-210	#8 x 7/8"	6, 7 or 8	1-1 1/4	3/16	1,000
50-230	#12 x 1"	9, 10 or 12	1-1 1/4	1/4	1,000
50-250	#16 x 1 3/8"	14 or 16, 1/4" Lag Screw	1 1/4-1 1/2	5/16	500
BULK					
50-239	#12 x 1"	9, 10 or 12	1-1 1/4	1/4	10,000

* When impact hammer drill is used, downsize drill hole 1/32".

Note: For maximum holding power, select screw length 1/4" longer than anchor.