

Issue Date: 7/25/2011

Page: 1 of 2

File: PSS-K1601PC-T1

15/25kV	200A Bushing Well	K1601PC-T1
---------	-------------------	------------



Features:

- 25kV, 200 Amp
- Conductive shield made of molded conductive EPDM makes positive ground contact with EPDM flange of bushing insert.
- Stainless steel flange resists corrosion and can be externally clamped or welded to apparatus.
- Epoxy structure with exceptionally high physical, electrical, and chemical resistance properties.
- Interface meets ANSI/IEEE 386 dimensional criteria for proper fit of mating parts.

K1601PC-T1

BUSHING WELL (For in- air application)

Applications:

Elastimold K1601-PC-T1-R series bushing wells are designed for in air application, and will universally accept Elastimold non-loadbreak bushing inserts, loadbreak bushing inserts, and the double bushing inserts. These are designed to be directly mounted in electrical apparatus on 200-Amp systems, through 25kV.

Typical applications would be in:

- Pad-mounted transformers
- Vault-type transformers
- Submersible transformers
- Switchgear

These bushing wells are available in shank lengths varying from 2.75" to 9.25" for either cover or side-mount installations. They are molded of epoxy and have a stainless steel flange for welding or externally clamping to the apparatus. A conductive rubber shield at the mating surface with connecting devices provides a fully-shielded, cable-to-apparatus connection. Reference Applicable Elastimold welding guide.

Ratings:

Meets ANSI/IEEE Standard 386, Latest Revision

For 25kV Voltage Class:


125kV BIL – Impulse Withstand (1.2 x 50 microsecond wave)
 40kV AC – One minute withstand
 78kV DC – 15 minutes withstand
 19kV AC – Corona Extinction @ 3pC sensitivity
 200 Amp – Continuous
 8 Hour Overload – 300 Amps, RMS
 12 Cycle Momentary – 15000 Amps, RMS, Asym
 3 Second Momentary – 3500 Amps, RMS, Sym

Issue Date: 7/25/2011

Page: 2 of 2

File: PSS-K1601PC-T1

15/25kV	200A Bushing Well	K1601PC-T1
---------	-------------------	------------



Ordering Instructions

To order a bushing well for in-air application through 25kV, select the shank length ("A" dimension) required and specify the style number shown below:

STYLE NUMBER	"A" SHANK LENGTH
K1601PC-T1	9.25"
K1601PC-T1-R	9.25"

Example:

The ordering number for a bushing well in-air with a shank length of 9.25" and permanent stud is K1601PC-T1

Note:

The bushing well is also available in removable stud well design "-R".

Each kit contains the following:

1	Epoxy Long Shank Well	K1601PC-T1
1	Silicone Lubricant	82-08
1	Instruction Sheet	IS-0061