

Issue Date: 10/04/2012

Page: 1 of 2

File: PSS-K650LB

25kV	600A Deadbreak Insulating Plug	K650LB
------	--------------------------------	--------



Features:

- Fully rated 25kV, 600 Amp Deadbreak Insulated Plug
- Part of an assembly that can be easily connected or disconnected using standard hand tools and equipment in a de-energized state
- Optional accessories allow visible external separation, by-pass, isolation, dead-ending, grounding, and testing as well as adding taps, surge arrestors, and circuit protection

K650LB Insulating Plug

Applications:

The K650LB is designed to provide a threaded mountable plug for use in cam-op cable joint kits. The K650LB is threaded onto the mounting surface and the retaining sleeves are threaded into bushing. The K650LB uses a standard IEEE 386 bushing interface for all connections and works with K655LR elbows and K655BE bushing extenders.

Ratings:

Meets ANSI/IEEE Standard 386, Latest Revision

For 25kV Voltage Class:


16.2kV Max Phase-to-Ground – Operating Voltage
 28kV Max Phase-to-Phase
 140kV BIL – Impulse Withstand (1.2 x 50 microsecond wave)
 45kV AC – One minute withstand
 84kV DC – 15 minutes withstand
 21.5kV AC – Corona Extinction @ 3pC sensitivity
 600 Amp – Continuous
 25kA Sym – 10 Cycles Momentary & Fault Close

Issue Date: 10/04/2012

Page: 2 of 2

File: PSS-K650LB

25kV	600A Deadbreak Insulated Plug	K650LB
------	-------------------------------	--------



Ordering Instructions:

To order 25kV, 600A insulated plug, specify **K650LB**.

Each kit contains the following:

1	Insulated Plug	K650LB
1	Tube, lubricant	82-08
1	Installation Instruction	IS-0409