

Issue Date: 03/25/2015

Page: 1 of 3

File: PSS-755L2-W0X

35 kV	600A Deadbreak 2 Way L-Kit	w/o Test Point	755L2
-------	----------------------------	----------------	-------



Features:

- Fully rated 35kV, 600 Amp Deadbreak 2 Way L-Kit
- Fully shielded, fully submersible molded rubber housing
- 100% peroxide-cured construction includes insulation and conductive EPDM materials
- Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state
- Optional accessories allow visible external separation, by-pass, isolation, dead-ending, grounding, and testing

755L2-W0X 2-Way L-Kit

Applications:

The 755L2-W0X elbow kit is comprised of two 755LR elbow connector, two 750BIP basic insulating plugs, two 755CA-W cable adapters, two 03700XXX compression lugs and one 750CP connecting plug. It is used to connect two cable ends and using the two insulating plugs as test points allows for capacitive voltage testing.


Ratings:

Meets ANSI/IEEE Standard 386, Latest Revision



For 35kV Voltage Class:

21.1kV Max Phase-to-Ground – Operating Voltage
 36.6kV Max Phase-to-Phase
 150kV BIL – Impulse Withstand (1.2 x 50 microsecond wave)
 50kV AC – One minute withstand
 103kV DC – 15 minutes withstand
 26kV AC – Corona Extinction @ 3pC sensitivity
 600 Amp – Continuous
 25kA Sym – 10 Cycles Momentary

35 kV	600A Deadbreak 2 Way L-Kit	w/o Test Point	755L2-W0X
-------	----------------------------	----------------	-----------



SIZE	INSULATION DIAMETER RANGE
G	19.30-24.13 .760-.950
H	21.59-26.67 .850-1.050
J	24.89-29.97 .980-1.180
K	27.69-33.27 1.090-1.310
L	29.97-37.21 1.180-1.465
LM	32.51-36.32 1.280-1.430
M	34.80-41.40 1.370-1.630
N	38.48-45.21 1.515-1.780
P	43.82-49.15 1.725-1.935
Q	48.26-53.85 1.900-2.120
R	53.72-56.77 2.115-2.235



35 kV	600A Deadbreak 2 Way L-Kit	w/o Test Point	755L2-W0X
-------	----------------------------	----------------	-----------

CATALOG NUMBER SELECTION

Step 1 (W)

Determine the insulation diameter of the cable. Select the insulation letter code that best straddles the insulation diameter from W table below. Insert code into catalog number.

Step 2

Choose the proper connector material type and insert it into the catalog number.

Step 3 (X)

Choose the proper compression lug code according to the conductor size from the Conductor Code Table. Insert code into catalog number.

Universal Al	0
CU	2
Bi-metal	5

755L2 -



Cable Insulation Diameter in inches		Cable Insulation Diameter in millimeters		Symbol for W
MIN.	MAX.	MIN.	MAX.	
0.760	0.950	19.304	24.130	G
0.850	1.050	21.590	26.670	H
0.980	1.180	24.892	29.972	J
1.090	1.310	27.686	33.274	K
1.180	1.465	29.972	37.211	L
1.280	1.430	32.512	36.322	LM
1.370	1.630	34.798	41.402	M
1.515	1.780	38.481	45.212	N
1.725	1.935	43.815	49.149	P
1.900	2.120	48.260	53.848	Q

X Code	AWG or kcmil		mm2	Connector Only		
	Strand./ Compr.	Solid/ Compact	Compact	Universal Aluminum	Copper	Bi-metal
210	-	2	-	03700210	03702210	04601210
220	2	1	35	03700220	03702220	04601220
230	1	1/0	50	03700230	03702230	04601230
240	1/0	2/0		03700240	03702240	04601240
250	2/0	3/0	70	03700250	03702250	04601250
260	3/0	4/0	95	03700260	03702260	04601260
270	4/0	250	125	03700270	03702270	04601270
280	250	300	-	03700280	03702280	04601280
290	300	350	150	03700290	03702290	04601290
300	350	400	185	03700300	03702300	04601300
310	400	450	240	03700310	03702310	04601310
320	450	500/550	-	03700320	03702320	04601320
330	500	600	250/300	03700330	03702330	04601330
340	550	650	-	03700340	03702340	04601340
350	600	700	400	03700350	03702350	03705350
360	650	750/800	-	03700360	03702360	04601360
380	700/750	900	-	03700380	03702380	04601380
390	800	-	500	03700390	03702390	04601390
400	900	1000	-	03700410	03702410	04601410
410	1000	-	-	03700410	03702410	04601410
420	-	1250	-	03700420	03702420	04601420
440	1250	-	-	03700440	03702440	04600440

Each kit contains the following:

2	Basic Elbow	755BLR
2	Cable Size Adapter	755CA-W
2	Universal Al. Compression Lugs	03700XXX
6	Tube, lubricant	82-08
2	Basic Insulating Plug	750BIP
2	Stud	750SA
1	Connecting Plug	750CP
1	Installation Instruction	IS-0230
1	Installation Instruction	IS-0244
1	Installation Instruction	IS-0915
1	Crimp Chart	CC-0050

Example:

The ordering number for a **600A 2 Way L-Kit** for a 4/0 compressed, 345 mil wall cable with an insulation diameter of 1.195" to 1.295" is **755L2-K0270**.

For: **900A 2 Way L-Kit**; please order:

755L2-H2270

NOTE. It is Mandatory for **900A** to have all the Components in Copper (Cable, connector and bushing, etc.)