

Issue Date: 12/16/2013

Page: 1 of 2

File: PSS-K655VSL3

15/25kV	600A Deadbreak 3-Way Vault Stretcher Kit	w/o Test Point	K655VSL3
---------	---	----------------	----------



Features:

- Fully rated 15/25kV, 600 Amp Deadbreak Vault Stretcher
- Fully shielded, fully submersible molded rubber housing
- 100% peroxide-cured construction includes insulation and conductive EPDM materials
- Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state
- Optional accessories allow visible external separation, by-pass, isolation, dead-ending, grounding, and testing as well as adding taps, surge arrestors, and fault current indicators

K655VSL3

3-Way Vault Stretcher Kit

Applications:

The K655VSL3 vault stretcher housing is a component of the Vault Stretcher product line. The K655VSL3 can be mated with the following components:

- K651CP
- K650BIP
- K650RTP
- K650RTW
- K650S1
- K650T1
- K650JX
- K650ETP


Ratings:

Meets ANSI/IEEE Standard 386, Latest Revision

For 15/25kV Voltage Class:

16.2kV Max Phase-to-Ground – Operating Voltage
 28kV Max Phase-to-Phase
 140kV BIL – Impulse Withstand (1.2 x 50 microsecond wave)
 45kV AC – One minute withstand
 84kV DC – 15 minutes withstand
 21.5kV AC – Corona Extinction @ 3pC sensitivity
 600 Amp – Continuous
 25kA Sym – 10 Cycles Momentary

15/25kV	600A Deadbreak 3-Way Vault Stretcher Kit	w/o Test Point	K655VSL3
---------	---	----------------	-----------------



Ordering Instructions:

To order 15/25kV, 600A 3-Way Vault Stretcher, specify **K655VSL3**.

Each kit contains the following:

1	Vault stretcher housing	K655VSL3
2	Insulating Plug w/ Cap	K650BIP
1	Connecting Plug	K650CP
1	Elbow connector housing	K65BLR
6	Tube, lubricant	82-08
1	Stud	650VSA
1	Installation Instruction	IS-0356
1	Installation Instruction	IS-0230

Example:

The ordering number for a 600 Amp 3-Way Vault Stretcher Kit is K655VSL3.