

Issue Date: 4/19/2013

Page: 1 of 2

File: PSS-776LR-W2X

35kV	900A Deadbreak Elbow	w/ Test Point	776LR-W2X
------	----------------------	---------------	-----------



Features:

- Fully rated 35kV, 900 Amp Deadbreak Elbow
- Fully shielded, fully submersible molded rubber housing
- 100% peroxide-cured construction includes insulation and conductive EPDM materials
- Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state
- Optional accessories allow visible external separation, by-pass, isolation, dead-ending, grounding, and testing as well as adding taps, surge arrestors, and fault current indicators
- Non-Corrosive Capacitive test point

776LR Elbow Connector (with Test Point)

Applications:

The Elastimold® 776LR (with test point) is designed to provide fully shielded, dead-front submersible cable connections to high-voltage apparatus. The 776LR can be used through 35kV with conductor range from #2 AWG to 1250 kcmil for aluminum and copper conductors and insulation diameters from .760" to 2.120". When used on metallic tape shield or drain wire cable, an ECS cable seal grounding device is recommended. The 776BLR can be mated with other Elastimold® products including the following:

- 775CP
- 775BIP
- 775ETP
- 775SOP
- 775S1
- 775J2, 775J3, 775J4


Ratings:

Meets ANSI/IEEE Standard 386, Latest Revision

For 35kV Voltage Class:

21.1kV Max Phase-to-Ground – Operating Voltage
 36.6kV Max Phase-to-Phase
 150kV BIL – Impulse Withstand (1.2 x 50 microsecond wave)
 50kV AC – One minute withstand
 103kV DC – 15 minutes withstand
 26kV AC – Corona Extinction @ 3pC sensitivity
 900 Amp – Continuous
 25kA Sym – 10 Cycles Momentary

35kV	900A Deadbreak Elbow	w/ Test Point	776LR-W2X
------	----------------------	---------------	-----------



776LR -

CU 2

W Code

XXX Code

Cable Insulation Diameter in inches		Cable Insulation Diameter in millimeters		Symbol for W
MIN.	MAX.	MIN.	MAX.	
0.760	0.950	19.304	24.130	G
0.850	1.050	21.590	26.670	H
0.980	1.180	24.892	29.972	J
1.090	1.310	27.686	33.274	K
1.180	1.465	29.972	37.211	L
1.280	1.430	32.512	36.322	LM
1.370	1.630	34.798	41.402	M
1.515	1.780	38.481	45.212	N
1.725	1.935	43.815	49.149	P
1.900	2.120	48.260	53.848	Q

Each kit contains the following:

1	Elbow connector housing	776BLR
1	Copper compression lug	03702XXX
1	Copper Stud	775SA
1	Insulated Plug w/ Cap	775BIP
3	Tube, lubricant	82-08
1	Cable adapter	755CA-W
1	Installation Instruction	IS-0230
1	Installation Instruction	IS-0244
1	Crimp chart	CC-0050

CATALOG NUMBER SELECTION

Step 1 (W)

Determine the insulation diameter of the cable.

Select the insulation letter code that best straddles the insulation diameter from W table below. Insert code into catalog number.

Step 2

Choose the proper connector material type and insert it into the catalog number.

Step 3 (X)

Choose the proper compression lug code according to the conductor size from the Conductor Code Table. Insert code into catalog number.

- For dimensions of the Stud, Insulating Plug, Lug, and Cable Adapter see individual spec. sheets

Example:

The ordering number for a 900 Amp Elbow Connector for a 4/0 compacted, 345 mil wall cable with an insulation diameter of 1.160" to 1.260" and test point is 776LR-K2270.

X Code	AWG or kcmil		mm2	Connector Only
	Strand./ Compr.	Solid/ Compact	Compact	Copper
210	-	2	-	03702210
220	2	1	35	03702220
230	1	1/0	50	03702230
240	1/0	2/0		03702240
250	2/0	3/0	70	03702250
260	3/0	4/0	95	03702260
270	4/0	250	125	03702270
280	250	300	-	03702280
290	300	350	150	03702290
300	350	400	185	03702300
310	400	450	240	03702310
320	450	500/550	-	03702320
330	500	600	250/300	03702330
350	600	700	-	03702350
360	650	750	400	03702360
380	700/750	900	-	03702380
390	800	-	-	03702390
400	900	1000	500	03702400
410	1000	-	-	03702410
420	-	1250	-	03702420
440	1250	-	-	03702440