


INSTALLATION INSTRUCTIONS

Roof Top support blocks with strut channel RTS6PG and RTS10PG

Superstrut®



Important

Read and understand all instructions and safety information before use. Be aware of proper usage and potential hazards.



CAUTION:

- Wear appropriate Personal Protective Equipment (PPE).

Installation instructions:

1. Surface preparation:

- From the work zone area, clear all debris and loose aggregate.
- For gravel roofs, remove gravel to ensure the blocks sit flush on the roof's surface.

Important: Check with the roofing manufacturer to see if an additional compatible isolation pad is required to maintain the roof's warranty.

2. Placement and spacing:

- Space support blocks according to local building codes or pipe manufacturer specifications (typically every 7 to 10 feet).
- Ensure the strut channel is perpendicular to the pipe run for even weight distribution.

3. Securing the load:

- Attach pipes or conduit by using standard strut clamps or straps sized (sold separately) for the application.
- Fasten hardware (sold separately) into the integrated galvanized strut channel.
- For heavy loads or bridging, use a secondary length of strut to connect two blocks.
- QR-Code below can be used to search for applicable strut accessories and to download the Superstrut catalog.



4. Final check:

- Confirm the blocks are level and do not obstruct roof drainage.
- In high-wind zones, consider mechanical tethering as specified by the engineer of record.

