

2



1

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

FINISHED GOOD PART NUMBER	FINISHED GOOD DESCRIPTION	COLOR	INPUT CORD LENGTH	WEIGHT
P16D21G	G6 MI PDU, 20AMP, (16)5-20R, NEMA 5-20P-3M, TOP FED, BLACK	BLACK (RAL 9005)	3M(+254MM/-127MM) 10' [+10"/-5"]	4.5kg

B

B

A

A

							WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY		SIGN DATE PRINT				
							TITLE INTELLIGENT SERIES PDU P16D21G CUSTOMER DRAWING						
							ITEM REVISION NAME						
							DATASHEET FILE NAME:						
							UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN] Tolerance(mm) 0<L<50 ±0.5 50<L<250 ±1.0 250<L<500 ±1.5 500<L<1000 ±2.5 1000<L<2000 ±4.0						
									THIRD ANGLE PROJECTION				
00A	09/20/2023	LWB	CSH	MJD	INITIAL RELEASE	P16D21G	DRAWN BY LWB		DATE 09/20/2023	CHK SEAN	SCALE NONE	MATERIAL/COLOR: N/A DRAWING NUMBER: P16D21G_DC	
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY LWB		DATE 09/20/2023	CHK SEAN	SCALE NONE	SHT 1 OF 1	SCALE B

2



1