

2

↑

1


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

FINISHED GOOD PART NUMBER	FINISHED GOOD DESCRIPTION	COLOR	INPUT CORD LENGTH	WEIGHT
P16E27G	G6 MS PDU, 16AMP, (12) C13 (4) C19, IEC 60309 2P 3W 6H IP44-3M, TOP FED, BLACK	BLACK (RAL 9005)	3M(+254MM-127MM) 10' [+10'/-5"]	5.5kg

2

↓

1

						WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATURE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY		SIGN DATE PRINT				
						TITLE INTELLIGENT SERIES PDU P16E27G-XXYZ CUSTOMER DRAWING						
						ITEM REVISION NAME:						
						DATASHEET FILE NAME:						
						UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]  THIRD ANGLE PROJECTION Tolerance(mm) 0<L<50 ±0.5 50<L<250 ±1.0 250<L<500 ±1.5 500<L<1000 ±2.5 1000<L<2000 ±4.0				MATERIAL/COLOR: N/A		
00A	09/21/2023	NW	CSH	MJD	INITIAL RELEASE	P16E27G-XXYZ	DRAWING NUMBER: P16E27G-XXYZ_DA					
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY NW	DATE 09/06/2023	CHK CSH	SCALE NONE	SHT 2 OF 2	SCALE B