



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


PANDUIT P/N	WEIGHT
SEE SHEET 2	SEE SHEET 2




REAR VIEW



TOP VIEW



FRONT VIEW



SIDE VIEW

SPECIFICATION:

1. STANDARD

UNIT TYPE: BASIC

ORIENTATION: HORIZONTAL (1U)

OUTLET QTY & TYPE: (6)C19

INPUT VOLTAGE: 200-240VAC

INPUT FREQUENCY: 50/60HZ

INPUT CURRENT: 30A(24A DERATED)

BREAKER QTY & TYPE: (3)20AMP, DOUBLE-POLE

INPUT PHASE: 3 PHASE DELTA ,L-L

RATED POWER: 8.6 kVA

INPUT PLUG: NEMA L15-30P 4W

INPUT POWER CORD: SEE SHEET 2 PART NUMBER TABLE

REGULATORY STANDARD: UL 498 COMPLIANT
2. ADDITIONAL:

NONE
3. ACCESSORIES:

PRODUCT SAFETY WARNING SHEET

QTY: (4) M6 × 12 PAN HEAD MACHINE SCREW


QTY: (4) M6 CAGE NUT

NOTES:

1. PRIMARY DIMENSIONS ARE IN MILLIMETERS.
2. SECONDARY DIMENSIONS ARE IN [INCHES]
3. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL,STATE,AND LOCAL CODES
4. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART
5. FOR FULL PRODUCT FUNCTIONALITY REFER TO USER MANUAL
6. DRAWING VIEWS SHOW THE INPUT CORD IN THE "TOP END FED" CONFIGURATION

IDENTIFICATION:


FOR FINISHED GOOD PART NUMBER & DESCRIPTION TABLE SEE SHEET 2 CONFIGURABLE PART NUMBERS: E06B49M-XXYZ



PLUG / RECEPTACLE BLOCK




PLUG
NEMA L15-30P 4W
30A, 250VAC MAX RATED INPUT



RECEPTACLE
IEC 60320 C19
16A, 240V MAX RATED OUTPUT

00A	03/04/2026	Mucl	MIM	MJD	INITIAL RELEASE	E06B49M
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN

PROJECT SPEC		SPS-EDI-611		PACKGING SPEC		1U-140mm	
PART NUMBER		E06B49M		WORK INSTRUCTION		RD-01-02-25	
INSPECTION INSTRUCTION NUMBER		QA-SIP-03		FMEA & CONTROL PLAN		PFMEA-P-01 CP-P-01	
TITLE INTELLIGENT SERIES PDU E06B49M CONTROL DRAWING							
ITEM REVISION NAME:							
DATASHEET FILE NAME:							
UNLESS OTHERWISE SPECIFIED DIENSIONAL TOLERANCE ARE :mm [IN] THIRD ANGLE PROJECTION Tolerance (mm) 0<L≤50 ±0.5 50<L≤250 ±1.0 250<L≤500 ±1.5 500<L≤1000 ±2.5 1000<L≤2000 ±4.0				MATERIAL/COLOR: N/A			
				DRAWING NUMBER: E06B49M_DC			
DRAWN BY		DATE	CHK	SCALE			
Mucl		03/04/2026	MIM	NONE		SHT 1 OF 2	
						SCALE B	

2

↑

1

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

FINISHED GOOD PART NUMBER	FINISHED GOOD DESCRIPTION	COLOR	INPUT CORD LENGTH	WEIGHT
E06B49M	BASIC PDU, 30A(24A DERATED), (6)C19, NEMA L15-30P 4W-3M,REAR-PED,BLACK	BLACK(RAL 9005)	3M(+254MM/-127MM)[10'(+10"/-5'')]	TBD

2

↓

1

00A	03/04/2025	Mucl	MIM	MJD	INITIAL RELEASE	E06B49M
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN

PROJECT SPEC		SPS-EDI-611		PACKGING SPEC		1U-140mm	
PART NUMBER		E06B49M		WORK INSTRUCTION		RD-01-02-25	
INSPECTION INSTRUCTION NUMBER		QA-SIP-03		FMEA & CONTROL PLAN		PFMEA-P-01 CP-P-01	
TITLE							
INTELLIGENT SERIES PDU E06B49M CONTROL DRAWING							
ITEM REVISION NAME:				PANDUIT			
DATASHEET FILE NAME:							
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]				MATERIAL/COLOR:			
THIRD ANGLE PROJECTION				N/A			
				DRAWING NUMBER:			
				E06B49M_DC			
				SCALE			
DRAWN BY	DATE	CHK	SCALE	SHT 2 OF 2		SCALE	
Mucl	03/04/2025	MIM	NONE			B	