

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT P/N	WEIGHT
SEE SHEET 2	SEE SHEET 2

SPECIFICATION:

1. STANDARD

UNIT TYPE: MONITORED INPUT
ORIENTATION: VERTICAL, 0U MID
OUTLET QTY & TYPE: (20)C13 , (4)C19
INPUT VOLTAGE: 200-240VAC
INPUT FREQUENCY: 50/60HZ
INPUT CURRENT: 30A(24A DERATED)
BREAKER QTY & TYPE: (2)20AMP, DOUBLE-POLE
INPUT PHASE: SINGLE-PHASE,L-L
RATED POWER: 5 KVA
INPUT PLUG: NEMA L6-30P 3W
INPUT POWER CORD: SEE SHEET 2 PART NUMBER TABLE
REGULATORY STANDARD: UL 498 COMPLIANT
2. ADDITIONAL:

NONE
3. ACCESSORIES:


PRODUCT SAFETY WARNING SHEET


NOTES:

1. PRIMARY DIMENSIONS ARE IN MILLIMETERS.
SECONDARY DIMENSIONS ARE IN [INCHES]
2. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE
NATIONAL,STATE,AND LOCAL CODES
3. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM
FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR
USE WITH THIS PART
4. FOR FULL PRODUCT FUNCTIONALITY REFER TO USER
MANUAL
5. DRAWING VIEWS SHOW THE INPUT CORD IN THE "TOP
END FED" CONFIGURATION


IDENTIFICATION:

FOR FINISHED GOOD PART NUMBER & DESCRIPTION TABLE SEE
SHEET 2 CONFIGURABLE PART NUMBERS: E24D07M-XXYZ



PROJECT SPEC		SPS-EDI-611		PACKGING SPEC		1490×56×56	
PART NUMBER		E24D07M		WORK INSTRUCTION		RD-01-02-25	
INSPECTION INSTRUCTION NUMBER		QA-SIP-03		FMEA & CONTROL PLAN		PFMEA-P-01 CP-P-01	
TITLE							
INTELLIGENT SERIES PDU E24D07M CONTROL DRAWING							
ITEM REVISION NAME:							
DATASHEET FILE NAME:							
UNLESS OTHERWISE SPECIFIED DIENSIONAL TOLERANCE ARE: mm [IN]				MATERIAL/COLOR:			
 THIRD ANGLE PROJECTION				N/A			
				DRAWING NUMBER:			
				E24D07M_DA			
				SHT 1 OF 3			
				SCALE			
DRAWN BY	DATE	CHK	SCALE	SCALE			
Mucl	06/01/2026	MIM	NONE	B			


01A	06/01/2026	Mucl	MIM	MJD	UPDATE COMPLIANCE LABEL	E24D07M
00A	03/04/2026	Mucl	MIM	MJD	INITIAL RELEASE	E24D07M
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN




PLUG / RECEPTACLE BLOCK



PLUG
NEMA L6-30P 3W
30A, 250VAC MAX RATED INPUT



RECEPTACLE
IEC 60320 C13
10A, 240V MAX RATED OUTPUT



RECEPTACLE
IEC 60320 C19
16A, 240V MAX RATED OUTPUT

2

↑

1

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

FINISHED GOOD PART NUMBER	FINISHED GOOD DESCRIPTION	COLOR	INPUT CORD LENGTH	WEIGHT
E24D07M	ES2P MI PDU, 30A(24A DERATED), (20)C13 (4)C19, NEMA L6-30P 3W-3M,TOP-FED, BLACK	BLACK(RAL 9005)	3M(+254MM/-127MM)[10'(+10"/-5")]	TBD

01A	06/01/2026	Mucl	MIM	MJD	UPDATE COMPLIANCE LABEL	E24D07M
00A	03/04/2026	Mucl	MIM	MJD	INITIAL RELEASE	E24D07M
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN

PROJECT SPEC		SPS-EDI-611		PACKGING SPEC		1490×56×56					
PART NUMBER		E24D07M		WORK INSTRUCTION		RD-01-02-25					
INSPECTION INSTRUCTION NUMBER		QA-SIP-03		FMEA & CONTROL PLAN		PFMEA-P-01 CP-P-01					
TITLE											
INTELLIGENT SERIES PDU E24D07M CONTROL DRAWING											
ITEM REVISION NAME:				PANDUIT							
DATASHEET FILE NAME:											
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCE ARE: mm [IN]				MATERIAL/COLOR:							
THIRD ANGLE PROJECTION				N/A							
				DRAWING NUMBER:							
				E24D07_DA							
				DRAWN BY		DATE		CHK		SCALE	
				Mucl		06/01/2026		MIM		NONE	
				SHT 2 OF 3		SCALE					
						B					

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT P/N	WEIGHT
SEE SHEET 2	SEE SHEET 2

SEE NOTE 3.

PANDUIT
18900 Panduit Drive, 60487, USA
www.panduit.com

Power Distribution Unit / Unidad de distribución de Energía



Model/Modelo: S1-DD024SV
Input/Entrada:200-240VAC,1Ø, 50/60Hz, 24A
Output per Outlet/Salida por Receptáculo:
C13; 200-240VAC, 10A per outlet
C19; 200-240VAC, 16A per outlet
24A Total
TAA COMPLIANT


CAN ICES-003(A)/NMB-003(A)
Exclusivo para uso interior.
Prohibido su uso en exteriores.
No modificar ni reparar.
Revisarla periódicamente.
Desconectarla cuando no se utilice.
No sobrepasar la corriente indicada.
Conectar la clavija totalmente.
Temperatura máxima de operación: 60°C
Calibre:15.3mm²

UPC & SKU Barcode

Serial # & MAC Address

Made in / Hecho en TAIWAN

COMPLIANCE LABEL




INTERNAL WIRING SCHEMATIC

- NOTES:
- INTERNAL WIRING:
WIRE TYPE: UL AWM 1015, 12 & 18AWG
LINE COLOR: BROWN
NEUTRAL COLOR: BLUE
EARTH GROUND COLOR: GREEN/YELLOW STRIPE
 - REFERENCE PANDUIT ENGINEERING PRODUCT SPECIFICATION SPS-EDI-611 FOR ADDITIONAL PRODUCT INFORMATION NOT SPECIFIED ON THIS DRAWING
 - FOR FINISHED GOOD PART NUMBER AND DESCRIPTION, SEE TABLE ON SHEET 2

LINE COLOR ANNOTATION IN SCHEMATIC:
RED:18AWG WIRE
PINK:12AWG WIRE
GREEN:3×10AWG WIRE
LIGHT BLUE: NETWORK CABLE
DARK BLUE: CT CABLE

01A	06/01/2026	Mucl	MIM	MJD	UPDATE COMPLIANCE LABEL	E24D07M
00A	03/04/2026	Mucl	MIM	MJD	INITIAL RELEASE	E24D07M
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN

PROJECT SPEC		SPS-EDI-611		PACKGING SPEC		1490×56×56			
PART NUMBER				E24D07M		WORK INSTRUCTION		RD-01-02-25	
INSPECTION INSTRUCTION NUMBER				QA-SIP-03		FMEA & CONTROL PLAN		PFMEA-P-01 CP-P-01	
TITLE									
INTELLIGENT SERIES PDU									
E24D07M									
CONTROL DRAWING									
ITEM REVISION NAME:									
DATASHEET FILE NAME:									
UNLESS OTHERWISE SPECIFIED						MATERIAL/COLOR:			
DIMENSIONAL TOLERANCE ARE: mm [IN]						N/A			
Tolerance (mm)									
0<L≤50 ±0.5									
50<L≤250 ±1.0									
250<L≤500 ±1.5									
500<L≤1000 ±2.5									
1000<L≤2000 ±4.0									
 THIRD ANGLE PROJECTION						DRAWING NUMBER:			
						E24D07M_DA			
DRAWN BY		DATE		CHK		SCALE			
Mucl		06/01/2026		MIM		NONE		SHT 3 OF 3	
								SCALE	
								B	