

59432J

UPC: 08593708161
 UNSPSC: 31162103
 Standard Qty: 100
 Master Carton Qty: 600
 Country of Origin: CHINA

#8-10-12 Yellow Winged Anchors, Plastic, Jar



Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	Plastic Anchor
Special Features	Plastic anchors are a more economical, light-duty part than steel hollow wall anchors.
Application	Designed to be used in sheetrock, plaster, brickwork, concrete, or tile. The shape of the collar allows plastic anchors to also be used in hollow materials.
Length	1.250"
Drill Size	1/4"
Material	Plastic
Finish	Yellow Dyed
Type	Plastic Wall Anchor
Material	Engineered Plastic
Application	Wall Anchor engineered for strength in a variety of materials. During installation, the screw extrudes and compresses the anchor into the base material. The anchor mold then conforms to the surface of the hole. These plastic anchors have good holding power by distributing the force over a larger surface area. It's plastic body makes it non-conductive making it great for electrical applications. Not recommended for overhead or high holding applications.
Screw Size Range	No. 8 to No. 14
Anchor Length	1-5/8"
Min. Hole Depth	2"
Min. Wall Thickness	1/2"
Drill Diameter	5/16
Uses	Electrical Equipment, Lighting Fixtures, Telephone Equipment, Alarms, Towel Dispensers, Circuit Breaks, and many more...

Compliance Information

Buy America Act Compliant: No
 Buy American Act Compliant: No
 RoHS Compliant: Yes
 UL Compliant:
 UL Code:

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Minerallac Company

Tel: 800-927-3293
 Fax: 800-824-8942
www.minerallac.com

59432J

UPC: 08593708161

UNSPSC: 31162103

Standard Qty: 100

Master Carton Qty: 600

Country of Origin: CHINA

#8-10-12 Yellow Winged Anchors, Plastic, Jar



WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.