

60016J

UPC: 08593798200

UNSPSC: 31162103

Standard Qty: 50

Master Carton Qty: 300

Country of Origin: VIETNAM

1/4 x 2-1/4" Hollow Wall Anchors, Short, Phillips/Slotted, Zinc Plated, Jar



Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	Hollow Wall Anchor
Special Features	When properly installed, they will not crack or crumble the wall material and resist vibration.
Application	Light-weight duty anchors to be with a pre-drilled hole in drywall, sheetrock, plaster, or paneling.
Diameter	1/4"
Length	2-1/4"
Drill Size	1/2"
Grip Range	5/8" – 1/8"
Head Type	Combo Phillips/Slotted
Material	Steel
Finish	Zinc Plated
Size	Short
Type	Sleeve Type Hollow Wall Anchor
Application	Sleeve type hollow wall anchor designed for use in base materials such as plaster, wallboard, or hollow tile. Removeable wall anchor that can be used for re-anchoring
Material	Carbon Steel
Anchor Size	1/4" Short
Screw Length	2-3/8"
Drive Size	#3
Drill Diameter	7/16"
Wall Thickness	1/2" to 5/8"
Drive Type	Slotted phillips round head
Ultimate Load Capacities (1/2" Wallboard)	200 lbs Tension, 200 lbs Shear
Allowable Load Capacities (1/2" Wallboard)	50 lbs Tension, 50 lbs Shear

Compliance Information

Buy America Act Compliant: No

Buy American Act Compliant: No

RoHS Compliant: Yes

UL Compliant:

UL Code:

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Minerallac Company

Tel: 800-927-3293

Fax: 800-824-8942

www.minerallac.com

60016J

UPC: 08593798200

UNSPSC: 31162103

Standard Qty: 50

Master Carton Qty: 300

Country of Origin: VIETNAM

1/4 x 2-1/4" Hollow Wall Anchors, Short, Phillips/Slotted, Zinc
Plated, Jar

WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.