

59425J

UPC: 08593798970
 UNSPSC: 31162101
 Standard Qty: 100
 Master Carton Qty: 1200
 Country of Origin: TAIWAN

#10-12 Green Plastic Plug Anchors, Jar



Product Attributes

Brand Name	Minerallac
Sub Brand	Cully
Type	Fluted Anchor
Special Features	The fluted plastic anchor is a light-duty part that can be used in stone, concrete, hollow block or brick.
Application	Not suited for applications where holding power is important and should not be installed in overhead areas. For use with self-tapping or wood screws.
Size	#10-12
Length	1.000"
Minimum Embedment Depth	1.000"
Drill Size	1/4"
Material	Engineered plastic
Tension Strength	In 4,000 PSI Concrete: 140
Shear Strength	In 4,000 PSI Concrete: 215
Type	Plastic Plug Anchor
Application	Designed for light duty fastening applications in concrete, block, brick or stone. The body of the Fluted Plastic anchor is injection molded from a ductile plastic and is designed to be used with sheet metal or wood screws. These fasteners are not recommended for use overhead or applications where holding values are critical.
Anchor Size	#10-12 x 1"
Color	Green
Material	Engineered Plastic
Drill Diameter	1/4"
Ultimate Load Capacities (2000 PSI Concrete)	440 lbs Tension, 280 lbs Shear
Allowable Load Capacities (2000 PSI Concrete)	110 lbs Tension, 70 lbs Shear

Compliance Information

Buy America Act Compliant: No
 Buy American Act Compliant: No
 RoHS Compliant: Yes
 UL Compliant:
 UL Code:

Proposition 65



☐ WARNING: This product can expose you to Phthalates, which is known to the State of California to cause cancer and reproductive harm. For more information go to www.P65Warnings.ca.gov.

Minerallac Company

Tel: 800-927-3293
 Fax: 800-824-8942
www.minerallac.com

59425J

UPC: 08593798970
UNSPSC: 31162101
Standard Qty: 100
Master Carton Qty: 1200
Country of Origin: TAIWAN

#10-12 Green Plastic Plug Anchors, Jar



WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.