

58902

UPC: 08593758902
 UNSPSC: 31161609
 Standard Qty: 25
 Master Carton Qty: 25
 Country of Origin: USA

1/2" Toggler® SnapToggle Toggle Bolt Anchors



Product Attributes

Brand Name	Toggler
Type	Hollow Wall Anchor
Special Features	Pre-assembled and ready for immediate use. Automatically adjusts to the thickness of the wall.
Application	For use with materials such as: gypsum board, drywall with a steel stud, concrete block, tile over drywall, etc.
Material	Steel
Finish	Zinc Plated
Length	Adjustable
Diameter	1/2"
Thread	UNC
Brand Name	Minerallac
Sub Brand	Cully
Type	Toggle Bolt
Use	Hollow Wall Anchor
Application	Heavy Duty hollow wall anchor designed for easy install in base materials such as plaster, wallboard, concrete block, plywood, and hollow tile
Anchor Size	1/2" x 4
Drill Diameter	3/4"
Wall Thickness	3/8"-2-1/2"
Installation	Requires a pre-drilled hole for proper install
Special Features	Pre-assembled and ready for immediate use. Automatically adjusts to the thickness of the wall
Ultimate Load Capacities (3/8" Wallboard)	140 lbs Tension, 290 lbs Shear
Allowable Load Capacities (3/8" Wallboard)	35 lbs Tension, 75 lbs Shear

Compliance Information

Buy America Act Compliant: Yes
 Buy American Act Compliant: Yes
 RoHS Compliant: Yes
 UL Compliant:
 UL Code:

Proposition 65

This product is in compliance with Prop65; it is not known to contain any chemicals associated with this regulation.

Minerallac Company

Tel: 800-927-3293
 Fax: 800-824-8942
www.minerallac.com

58902

UPC: 08593758902

UNSPSC: 31161609

Standard Qty: 25

Master Carton Qty: 25

Country of Origin: USA

1/2" Toggler® SnapToggle Toggle Bolt Anchors



WARRANTY DISCLAIMER The information, data and recommendations contained herein may not be all inclusive or specific to your situation, and should only be used as a guide. The information is furnished upon the condition that the person receiving it shall make his/her own determination of the suitability of the product for his/her particular use and on condition that they assume the risk of the use thereof.

With respect to this publication and the product related thereto, except otherwise expressly provided by Manufacturer in writing, MANUFACTURER MAKES NO EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

Remedy/Liability Limits The exclusive remedy for losses or damages resulting from this publication or the related product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's sole election, one of the following: 1. Refund of purchase price paid by buyer or user for product bought, or 2. Replacement of amount of product used.

Manufacturer shall not be liable for losses or damages resulting from use of this publication or handling or use of this product, IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES, OR LOST PROFITS.

The terms of this Warranty Disclaimer and Remedy/Liability Limits cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this Warranty Disclaimer or Limitation of Remedies in any manner.