





With 115 mm x 61 mm x 113 mm, our industrial splice box is by far smaller than comparable 19" solutions.

Its inner values are really convincing as well so that the installation is quite simple and done very fast. FIMP-M is ready for splicing and contains splice tray, couplings, pigtails and cable gland. Regarding different couplings, you can choose from SMA, ST, SC, LC, FC-PC, SC-RJ and E-2000. The front panel and the splice cassette can be removed for splicing and since the cassette is magnetizable, it can easily be fixed onto a splice unit. The cassette has got a hole for splice units with a bolt.

The powder coated stainless steel housing is also magnetizable so that the splice box can easily be affixed to another housing or to a switch cabinet in case of no different tray. Furthermore, FIMP has got a clip for DIN rail mounting (35mm) and optional a kit for wall fastening. Thus, there are space-saving and flexible solutions for mounting our FIMP.



Different colours of housing and couplings

Type MM	6xST Duplex 62MM	6xSC Duplex 62MM	3xLC Quattro 62MM	6xE2000 Duplex 62MM	6xST Duplex 50MM	6xSC Duplex 50MM	3xLC Quattro 50MM	6xE2000 compact 50MM	
Article no.	06000 22196-00	06000 22396-00	06000 22493-00	06000 22596-00	06000 12196-00	06000 12396-00	06000 12493-00	06010 12796-00	
Type SM	6xST Duplex	6xSC Duplex	6xSC Duplex 8° APC	3xLC Quattro	6xE2000 compact	6xE2000 duplex 8° APC			
Article no.	06000 36196-00	06000 36396-00	06000 38396-00	06000 36493-00	06010 36796-00	06010 38796-00			
Weight	450 g								
Dimensions	Height: 115 mm; Width: 61 mm; Depth: 113 mm								
Operating Temperature	-40 °C – +75 °C								
Humidity	10% – 95 % relative, non condensing								
Housing	Stainless steel, powder coated								
Accessories	Article no.	Description							
	1060000001	Cable gland M20							
	1060000002	Nut M20							
	1060000013	Strain relief							
	1060000020	Front panel SC Duplex, not assembled							
	1060000021	Front panel SC-RJ, not assembled							
	1060000022	Splice holder							
	1060000023	Splice protection							
	1060000009	Countersunk screw M 2,5x6							
	1000000001	Screws							
	1060000002	Dual Mount Kit							
	1060000010	Lens tapping screw for fixing front panel, Philipps screw, 2,2 x 9,5 mm							