



Search Submit

[Advanced Part Search](#)

- [Home](#)
- [News & Events](#)
- [Products](#)
 - [Mild Steel Enclosures \(Type 12, 4\)](#)
 - [Stainless Steel Enclosures \(Type 4X\)](#)
 - [Aluminum Enclosures \(Type 4X\)](#)
 - [Non-Metallic Enclosures \(Type 4X\)](#)
 - [Disconnect Enclosures](#)
 - [Modular Freestanding Enclosures](#)
 - [Operator Interface Enclosures](#)
 - [Wireway & Trough](#)
 - [Commercial Enclosures](#)
 - [Climate Control](#)
 - [Data Communication Infrastructure](#)
 - [General Accessories](#)
- [Distributors](#)
- [Resources](#)
 - [New Products](#)
 - [Product Guide](#)
 - [HammondConnect \(Partner Portal\)](#)
 - [Climate Control Sizing Software](#)
 - [Technical Information](#)
 - [Compliance Information](#)
 - [Warranty Information](#)
 - [Enclosure Overview](#)
 - [Videos](#)
- [Literature](#)
- [Corporate](#)
 - [About Hammond](#)
 - [Logo Downloads](#)
 - [Career Opportunities](#)
 - [Investor Information](#)
 - [Press Releases](#)
- [Contact Us](#)

Fluorescent Light Kit & Accessories *FLK Series*

English | [Français](#)

[Home](#) / [Electrical](#) / [General Accessories](#) / [Archive](#) /

Note: This product line has been discontinued as a stocked series. Information is for reference only. For alternative solution assistance, please [contact Hammond here](#) or call: USA (716) 630-7030, Canada and International (519) 822-2960.

- [Profile Image](#)

CSA

UL



 Hardware Included

 Restriction of Hazardous Substances Compliant

Product Resources

- [Specification Sheet](#)
- [Print Page](#)
- [Contact Us](#)

Share this Product

 [Share via email](#)  [Share on Facebook](#)  [Share on X](#)  [Share on LinkedIn](#)

Features

- Please see alternatives [here](#)
- Light kits are offered in 18", 24", and 48" widths.
- CSA and UL component recognized.
- Operating voltage 115 AC 60Hz
- Features a manually operated switch, 115V convenience outlet, durable plastic lens, and 6 foot power cord (without plug).
- Can be mounted into light mounting channel, bolt through enclosure, or by using magnet strip (available separately - see chart below).
- 1¾" high x 4½" deep.
- Finished in white.
- Use standard 18", 24", or 48" T8 fluorescent bulb (not included).
- Magnet mount kit can be used with mild steel enclosures only.

Accessories

-  [Remote Door Switches](#)

Part Details

Click Part No., below, for details (e.g., Product drawings, assembly instructions, ship weight)

Magnetic Mount Kit Replacement Lens Kit			
Part No.	Description	Part No.	Part No.
FLK18T8¹	18" Fluorescent Light Kit 115V	FLK18MM	FLK18LENSE
FLK24T8¹	24" Fluorescent Light Kit 115V	FLK18MM	FLK24LENSE
FLK48T8¹	48" Fluorescent Light Kit 115V	FLK48MM	FLK48LENSE

¹ T8 fluorescent bulb not included

[Need Assistance? Contact Us.](#)

Data subject to change without notice.

Tags: [light kit](#), [fluorescent](#), [lighting](#), [lens](#), [115V](#), [outlet](#)

- [Home](#)

- [Back to Top](#)
- [Contact Us](#)
- [Distributors](#)
- [HammondConnect \(Partner Portal\)](#)
- [Login](#)
- [Facebook](#)
- [Instagram](#)
- [LinkedIn](#)
- [YouTube](#)

© 2026. Hammond Manufacturing Ltd. All rights reserved.