



Search Submit

[Advanced Part Search](#)

- [Home](#)
- [News & Events](#)
- [Products](#)
 - [Mild Steel Enclosures \(Type 12, 4\)](#)
 - [Stainless Steel Enclosures \(Type 4X\)](#)
 - [Aluminum Enclosures \(Type 4X\)](#)
 - [Non-Metallic Enclosures \(Type 4X\)](#)
 - [Disconnect Enclosures](#)
 - [Modular Freestanding Enclosures](#)
 - [Operator Interface Enclosures](#)
 - [Wireway & Trough](#)
 - [Commercial Enclosures](#)
 - [Climate Control](#)
 - [Data Communication Infrastructure](#)
 - [General Accessories](#)
- [Distributors](#)
- [Resources](#)
 - [New Products](#)
 - [Product Guide](#)
 - [HammondConnect \(Partner Portal\)](#)
 - [Climate Control Sizing Software](#)
 - [Technical Information](#)
 - [Compliance Information](#)
 - [Warranty Information](#)
 - [Enclosure Overview](#)
 - [Videos](#)
- [Literature](#)
- [Corporate](#)
 - [About Hammond](#)
 - [Logo Downloads](#)
 - [Career Opportunities](#)
 - [Investor Information](#)
 - [Press Releases](#)
- [Contact Us](#)

Type 4, 4X Polyester Pushbutton Enclosure *PJPB Series*

English | [Français](#)

[Home](#) / [Electrical](#) / [Operator Interface](#) / [Pushbutton Enclosures](#)

- [PJPB Group](#)

CSA

UL

Restriction of Hazardous Substances Compliant



Product Resources

- [Specification Sheet](#)
- [Print Page](#)
- [Contact Us](#)

Links

- [Part Details \(2D/3D CAD\)](#)
- [Similar Products](#)
- [Alternate Materials](#)

Share this Product

 [Share via email](#)  [Share on Facebook](#)  [Share on X](#)  [Share on LinkedIn](#)

Application

- Designed for use as pushbutton enclosures for 22.5mm or 30.5mm devices.
- Provides outstanding insulation and protection where equipment may be hosed down or be very wet.
- Ideal in applications with high temperatures or highly corrosive environments.

Standards

- UL 508A Type 1, 2, 3, 4, 4X, 12 and 13
- CSA Type 1, 2, 3, 4, 4X, 12 and 13
- **Complies with**
 - NEMA Type 1, 2, 3, 4, 4X, 12 and 13
 - IEC 60529, IP66

Construction

- Molded fiberglass polyester enclosure with matching cover is easily punched, cut, or drilled.
- Cover is fastened with captive stainless steel screws in threaded brass inserts.
- Captive oil resistant gasket provides a positive seal.
- Mounting through rear holes on enclosure. Use #8 x 1 inch screw (not included).
- Enhanced UV inhibitors protect against outdoor weathering.
- Operating temperatures between 130°C and -40°C (266°F to -40°F).
- Impact index of 6.78J (5 ft/lb).
- For corrosion resistance information, please refer to table in Technical Information.

Finish

- Fiberglass polyester material has a gray finish.
- Optional aluminum inner panel natural finish.

Accessories

-  [Hole Plugs](#) [Hole Plugs](#)

 [Gallery Image](#)

Part Details

Click [Part No.](#), below, for details (e.g., Product drawings, assembly instructions, ship weight)

Units shown: **inch**. Switch units to: [mm](#)

30.5mm PB		22.5mm PB	# of	Enclosure			Optional Aluminum Panel		
Part No.	Part No.	Holes	H	W	D	Part No.	H	W	
PJ744P1	PJ744P221	1	6.74	3.93	3.88	PJP74	4.00	3.13	
PJ744P2	PJ744P222	2	6.74	3.93	3.88	PJP74	4.00	3.13	
PJ944P3	PJ944P223	3	8.99	3.93	3.88	PJP94	6.25	3.13	

Similar Products

-  [Type 4, 4X Polyester Pushbutton Enclosure](#)
[Type 4, 4X Polyester Pushbutton Enclosure](#)
PJPBLC Series

Alternate Materials

-  [Type 4, 4X Polycarbonate Pushbutton Enclosure](#)
[Type 4, 4X Polycarbonate Pushbutton Enclosure](#)
1554 PB Series

[Need Assistance? Contact Us.](#)

Data subject to change without notice.

Tags: [pushbutton](#), [non-metallic](#), [polyester](#), [Type 4X](#), [Type 6P](#), [IP66](#), [22mm](#), [30.5mm](#)

- [Home](#)
- [Back to Top](#)
- [Contact Us](#)
- [Distributors](#)
- [HammondConnect \(Partner Portal\)](#)
- [Login](#)
- [Facebook](#)
- [Instagram](#)
- [LinkedIn](#)
- [YouTube](#)