
THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


MATERIAL	HIGH CONDUCTIVITY SEAMLESS COPPER TUBE
PLATING	ELECTRO-TIN
WIRE SIZE	6 AWG
WIRE TYPE	STRANDED COPPER; CLASS B: COMPACT, COMPRESSED OR CONCENTRIC, CLASS C: CONCENTRIC.
WIRE STRIP LENGTH	1-1/8 IN.
STUD SIZE	1/4 IN.
UL LISTED WIRE CONNECTOR	YES, FOR APPLICATIONS UP TO 35KV. CONSULT CABLE MANUFACTURER FOR VOLTAGE STRESS RELIEF INSTRUCTIONS WITH APPLICATIONS GREATER THAN 2000 VOLTS.
UL TEMPERATURE RATING	90° C
CSA CERTIFIED WIRE CONNECTOR	YES
PANDUIT COLOR CODE ON BARREL	BLUE
PANDUIT DIE INDEX NO. ON BARREL	P24
ALTERNATE INDUSTRY DIE INDEX NO. () ON BARREL	(7)


DIMENSIONS IN BRACKETS ARE MILLIMETERS

LISTED
WIRE CONNECTOR

CERTIFIED







REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
02A	06-05-26	ANVM	ANVM	JSUN	C. ADDED HOLE POSITION DIMENSION AND NOTE. B. REVISED DRAWING NUMBER: N10883WU-DC WAS LCC6-14JAWH-CUST. A. CONVERTED TO NX.	042112/00
01	01-01-07	JHNU	JHNU	–	REVISED BARREL O.D. AND I.D.	PC00644

PART NUMBER: LCC6-14JAWH-L

TITLE: LCC6-14JAWH-L COPPER LUG - SLOTTED TWO-HOLE, LONG BARREL WITH WINDOW, 45° ANGLE TONGUE

CUSTOMER DRAWING

ITEM REVISION NAME: N10883WU/00

DATASET FILE NAME: N10883WU-DC r02A

THIRD ANGLE PROJECTION

MATERIAL: SEE TABLE

DRAWING NUMBER: N10883WU-DC

DRAWN BY	DATE	CHK	SCALE	SIZE
JHNU	01-01-07	JHNU	NONE	B

SHEET 1 OF 1

B_SIZE_CUSTOMER_LAND