Type 4X Polyester Wallmount Enclosure *PJW Series*

Continuous Hinge Door with Twist Latches and 3 Pt Handle

Panel Sold Separately

Application

- Designed for use as instrument enclosures, electric, hydraulic or pneumatic control housings, electrical junction boxes or terminal wiring enclosures.
- Provides outstanding insulation and protection where equipment may be hosed down or be very wet.
- Ideal in applications with high temperatures or highly corrosive environments.

Standards

- UL/cUL 508A Type 1, 2, 3, 4, 4X, 12 and 13
- cUL Type 1, 2, 3, 4, 4X, 12 and 13 per CSA 22.2 No. 94
- Complies with
  - NEMA Type 1, 2, 3, 4, 4X,12 and 13
  - IEC 60529, IP66

Construction

- Molded fiberglass polyester enclosure with matching cover is easily punched, cut, or drilled.
- Enhanced UV inhibitors protect against outdoor weathering.
- 3/8 collar studs are provided for optional inner panel mounting, hardware included. Note: Sizes 36x36" and larger have 8 collar studs for added stiffness.
- Stainless steel butterfly type "twist latch" door fasteners with padlock provision.
- Captive oil resistant gasket provides a positive seal.
- Integrated mounting flange.
- Operating temperatures between 130°C and -40°C (266°F to -40°F).
- Impact index of 6.78J (5 ft/lb).
- For corrosion resistance information, please refer to table in the **Technical Information** section.

Finish

- Fiberglass polyester material has a gray finish.
- Optional inner panels are available in white powder coated finished steel.

Accessories

- Additional Inner Panels
- Window Kits
- General Accessories
- Pole Mounting Kit
- Climate Control

New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

Latch	3 Pt Handle	Enclosure			Optional Inner Panel		
Part No.	Part No.	H	W	D	H	W	Part No.
PJEC363012T	**PJEC3630123PT**	36.48	30.50	12.18	33.00	27.00	**18P3327**
PJEC363012TW	**PJEC3630123PTW**	36.48	30.50	12.18	33.00	27.00	**18P3327**
PJW363014L	**PJW363014L3PT**	36.25	30.25	14.13	33.00	27.00	**18P3327**
PJW363610L	**PJW363610L3PT**	36.25	36.25	10.13	33.00	33.00	**18P3333**
PJW363614L	**PJW363614L3PT**	36.25	36.25	14.13	33.00	33.00	**18P3333**
PJW483610L	**PJW483610L3PT**	48.25	36.25	10.13	45.00	33.00	**18P4533**
PJW483614L	**PJW483614L3PT**	48.25	36.25	14.13	45.00	33.00	**18P4533**
PJW603610L	**PJW603610L3PT**	60.25	36.25	10.13	57.00	33.00	**18P5733**
PJW603614L	**PJW603614L3PT**	60.25	36.25	14.13	57.00	33.00	**18P5733**

Parts ending in W have window. Alternative inner panel options also available.

Tags: **PJ**, **polyester**, **fiberglass**, **non-metallic**, **window**, **wallmount**, **NEMA 4X**, **Type 4X**, **outdoor**, **continuous hinge**, **twist latch**, **3 point handle**, **nema box**

Data subject to change without notice.

© 2026. Hammond Manufacturing Ltd. All rights reserved.