

Representative Image

Catalog No. TH4364

Description: 200A 3P HD N1 600V FUSIBLE SWITCH

UPC No 783164604825

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type HD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism.
- 60/75°C conductor rating.
- Full cover interlocks.

Descriptors

Category	Heavy Duty
GO Schedule	S1

Specifications

Amperage	200 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Options	None
Wire Range (Cu/Al)	2-250
480 Vac, NEC Std, 1-ph	25 hp
480 Vac, NEC Std, 3-ph	50 hp
480 Vac, Time Delay, 1-ph	50 hp
480 Vac, Time Delay, 3-ph	125 hp
600 Vac, NEC Std, 1-ph	30 hp
600 Vac, NEC Std, 3-ph	60 hp
600 Vac, Time Delay, 1-ph	50 hp
600 Vac, Time Delay, 3-ph	150 hp
250 Vdc	40 hp

Classifications

cUL Listed	Yes
UL Listed	Yes

Dimensions

Height	31,5 in

by ABB

Dimensions	
Depth	5,1 in
Width	13,3 in
Weight	33 lb