
Bridgeport Fittings Inc.
705 Lordship Blvd.
Stratford, CT 06615

Phone: 203-377-5944
Fax: 203-381-3488

Malleable

Images





Download Photo Image Download Dimensional Image

Dimension A in Inches:	2.455
Dimension B in Inches:	1.186
Dimension C in Inches:	5.613
Dimension D in Inches:	4.683

Application

45 Degree connector for use with metallic liquid tight conduit. Liquidtight connectors are suitable for use in Class I, Div 2; Class II, Div 1 and 2; and Class III, Div 1 and 2 hazardous locations.

Product Information

Material:	Malleable Iron
Finish:	Zinc Electro-Plate

Certifications & Codes:

Federal Specification Number:	A-A-50552
NEMA Standard:	FB-1
UL File Number:	E9391, cULus
UL Standard:	UL-514B
UNSPSC:	39121420

Catalog ID: 459-SLT

UPC Number: 78174702459

Description: Connector, Liquid Tight, 45 Degree, Size 4 Inch

Application: 45 Degree connector for use with metallic liquid tight conduit. Liquidtight connectors are suitable for use in Class I, Div 2; Class II, Div 1 and 2; and Class III, Div 1 and 2 hazardous locations.

Trade Size: 4"

Std Pkg Qty: 1

Unit Qty: ----