



Representative Image

Catalog No. TL30422C

Description: MLO 225A 30CRT 3P4W 208Y/120V COMBO

UPC No 783164189933

Home > Load Center & Meter Combos > Load Centers

Main lug load centers can be used as a home's main panel or sub panel depending upon your preferences. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TL30422C features space for 30, 1" breakers, 3 phases, a 225 A bus ampere rating, and a combination/flush enclosure.

Descriptors

Category	Load Centers
GO Schedule	R7

Specifications

# Branch Circuit 250A	30
1" Space	30
1/2" Space	0
Amperage	225 A
Circuit Breaker Style	Plug-In
Device type	Main Lug
Door	Yes
Enclosure	Indoor
Enclosure Type	Indoor, Combination
Factory Installed Ground Kit	No
Feed	Either
Input/Output Voltage	208Y/120V ac
Interrupting Capacity Rating	65
Load Center Type	Standard
NEMA Rating	NEMA 1
Phase	3 Phase
Service & Voltage	3 Phase, 4 Wire, 208Y/120V ac
Wires	4 Wire

Classifications

UL/CUL Listing	UL
----------------	----

Dimensions

Height	33.2 in
Weight	31.1 lb
Width	14.0 in

by ABB

