



Representative Image

## Alternate Catalog No. X250-B4-48-XD Catalog No. 3AUA0000226366

**Description: PSTX ENCLOSED 250HP 480V TYPE4 XD**

**UPC No 6438177522430**

**Home > Soft Starters > Softstarter - Enclosed (PSTX)**

PSTX extreme duty enclosed softstarters are the ultimate softstarting solution. Includes all features of the PSTX normal duty, sized for heavy duty applications, plus an AC-3 emergency bypass. Both the PSTX softstarter and TMAX XT breakers are utilized. Door mounted pilot devices include PSTX keypad, hand-off-auto selector switch, start and stop pushbuttons, power on pilot light, run pilot light, fault pilot light, normal/emergency bypass selector switch, emergency bypass start and stop pushbuttons and emergency bypass pilot light. Good for Normal Duty class 10 starts for 300HP/361A, heavy duty class 30 starts for 250HP/302A, SSCR rating of 65kA, 480V and type 4 enclosure.

### Descriptors

|          |                               |
|----------|-------------------------------|
| Category | Softstarter - Enclosed (PSTX) |
|----------|-------------------------------|

### Specifications

|                                |                 |
|--------------------------------|-----------------|
| Enclosure Type                 | NEMA 4          |
| Motor Voltage                  | 480 V           |
| Motor HP at 460V- Extreme duty | 250             |
| Protection Type                | Circuit Breaker |
| Power Dissipation In Watts     | 260             |
| Height (Inches)                | 48              |
| Width (Inches)                 | 36              |
| Depth (Inches)                 | 16              |

### Dimensions

|             |        |
|-------------|--------|
| Weight (lb) | 314    |
| Height (mm) | 1219,2 |
| Depth (mm)  | 406,4  |
| Weight (kg) | 142    |