



Representative Image

## Catalog No. TDT3322R

**Description: 60A 3P DBL THR N3R 240V FUSIBLE**

**UPC No 783164069372**

**Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Double Throw**

When it comes to getting the job done right, you can count on safety switches from ABB. ABB offers a wide variety of general duty switches for residential and light commercial purposes, while the extensive line of heavy-duty switches is best suited for commercial and industrial applications. For the toughest industrial environments — such as cement foundries, steel mills and processing plants — dust-tight and stainless steel switches are available. We also offer a variety of double throw switches for emergency generators. No matter the application, we've got you covered with a rugged, reliable and easy-to-install Spec-Setter safety switch. 60A 3P DBL THR N3R 240V FUSIBLE

### Descriptors

|             |              |
|-------------|--------------|
| Category    | Double Throw |
| GO Schedule | SB           |

### Specifications

|                           |                   |
|---------------------------|-------------------|
| Voltage                   | 240 AC            |
| Amperage                  | 60 A              |
| Poles                     | 3                 |
| Wires                     | 3                 |
| Fusing                    | Fusible           |
| Enclosure                 | NEMA 3R (Outdoor) |
| Options                   | None              |
| Wire Range (Cu/Al)        | 14-2 (Cu/Al)      |
| 240 Vac, Time Delay, 1-ph | 10 hp             |
| 240 Vac, Time Delay, 3-ph | 15 hp             |
| 480 Vac, Time Delay, 1-ph | 20 hp             |
| 480 Vac, Time Delay, 3-ph | 30 hp             |
| 600 Vac, Time Delay, 1-ph | 25 hp             |
| 600 Vac, Time Delay, 3-ph | 50 hp             |
| 250 Vdc                   | 10 hp             |
| GSA Compliance            | No                |

### Classifications

|            |     |
|------------|-----|
| cUL Listed | Yes |
| UL Listed  | Yes |

### Dimensions

|        |          |
|--------|----------|
| Height | 37.00 in |
| Width  | 12.75 in |
| Weight | 47 lb    |

**by ABB**