



360°

Representative Image

## Alternate Catalog No. VBC6-30-10-P01 Catalog No. GJL1213909R0101

**Description:** VBC6-30-10-P-01 Mini Rev.Contactor 24VDC

**UPC No** 4013614053818

**Home > Contactors & Starters > UL Listed IEC Contactors > AF Contactors**

The VBC6-30-10-P mini reversing contactor is a compact 3 pole contactor with 1 auxiliary contact, soldering pins and normal mechanical interlock. They are ideally suited for applications where reliability is a must and space is at a premium. Mini reversing contactors are used in residential buildings, commercial buildings and industrial applications for the control of three-phase motor loads up to 4 kW (AC-3). Further features are the noiseless and hum-free coil, a switch position indication and the integrated possibility for rail mounting.

### Descriptors

|          |               |
|----------|---------------|
| Category | AF Contactors |
|----------|---------------|

### Specifications

|                                                    |                                                                                                                                                        |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Type                                       | Mini Contactors (B6, B7)                                                                                                                               |
| General Use Rating UL/CSA                          | (300 V AC) 8 A                                                                                                                                         |
| Object Classification Code                         | Q                                                                                                                                                      |
| Terminal Type                                      | Soldering Pins                                                                                                                                         |
| Rated Control Circuit Voltage                      | 24 V DC                                                                                                                                                |
| Number of Main Contacts NO                         | 3                                                                                                                                                      |
| Number of Main Contacts NC                         | 0                                                                                                                                                      |
| Maximum Operating Voltage UL/CSA                   | Main Circuit 600 V AC                                                                                                                                  |
| Resistance to Vibrations acc. to IEC 60068-2-6     | 5g / 5 ... 150 Hz                                                                                                                                      |
| Number of Auxiliary Contacts NO                    | 1                                                                                                                                                      |
| RoHS Status                                        | Following EU Directive 2011/65/EU                                                                                                                      |
| Reference Ambient Air Temperature                  | Operation -20 ... +55 °C                                                                                                                               |
| Rated Operational Voltage                          | Main Circuit 690 V AC                                                                                                                                  |
| Resistance to Shock acc. to IEC 60068-2-27         | 11 ms Pulse 15g                                                                                                                                        |
| Number of Auxiliary Contacts NC                    | 0                                                                                                                                                      |
| Maximum Operating Altitude Permissible             | 2000 m                                                                                                                                                 |
| Rated Operational Current AC-1                     | (220 / 240 V) 40 °C 12 A<br>(220 / 240 V) 55 °C 12 A<br>(380 / 440 V) 40 °C 12 A<br>(380 / 440 V) 55 °C 12 A<br>(690 V) 40 °C 6 A<br>(690 V) 55 °C 6 A |
| Standards                                          | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>IEC/EN 60947-5-1<br>UL 60947-1<br>UL 60947-4-1                                                                   |
| Rated Operational Power AC-3                       | 4 kW<br>(220 / 230 / 240 V) 2.2 kW<br>(400 V) 4 kW<br>(440 V) 4 kW<br>(500 V) 4 kW<br>(690 V) 3 kW                                                     |
| Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1 | 8 x I <sub>e</sub> / AC-3                                                                                                                              |

by **ABB**

## Specifications

|                                                  |                                                                                                                                                                                            |
|--------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Horsepower Rating UL/CSA                         | (208 V AC) Three Phase 1 hp<br>(220 ... 240 V AC) Single Phase 0.5 hp<br>(220 ... 240 V AC) Three Phase 2 hp<br>(440 ... 480 V AC) Three Phase 3 hp<br>(550 ... 600 V AC) Three Phase 1 hp |
| Conventional Free-air Thermal Current            | Main Circuit 12 A                                                                                                                                                                          |
| Rated Frequency                                  | Control Circuit DC<br>Main Circuit 60 Hz<br>Main Circuit 50Hz<br>Main Circuit DC                                                                                                           |
| Rated Short-time Withstand Current               | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 64 A                                                                                                                            |
| Rated Operational Current AC-3                   | (220 / 230 / 240 V) 55 °C 9 A<br>(380 / 400 V) 55 °C 8.5 A<br>(440 V) 55 °C 8 A<br>(500 V) 55 °C 5.5 A<br>(690 V) 55 °C 3.5 A                                                              |
| Rated Making Capacity AC-3 acc. to IEC 60947-4-1 | 10 x I <sub>e</sub> / AC-3                                                                                                                                                                 |
| Maximum Electrical Switching Frequency           | AC-1 300 cycles per hour<br>AC-15 600 cycles per hour<br>AC-3 600 cycles per hour<br>DC-1 600 cycles per hour<br>DC-13 600 cycles per hour<br>DC-3 600 cycles per hour                     |
| Rated Insulation Voltage                         | 690 V<br>acc. to UL/CSA 600 V                                                                                                                                                              |
| Mechanical Durability                            | 10000000 cycle                                                                                                                                                                             |
| Coil Operating Limits                            | (acc. to IEC 60947-4-1) for DC supply 0.85 ... 1.1 x U <sub>c</sub> (at $\theta \leq 55^\circ \text{C}$ )                                                                                  |
| Secondary Rated Impulse Withstand Voltage        | Main Circuit 6 kV                                                                                                                                                                          |
| Coil Consumption                                 | Average Holding Value DC 3.5 W<br>Average Pull-in Value DC 3.5 W                                                                                                                           |
| Degree of Protection                             | Control Circuit Terminals IP20<br>Main Circuit Terminals IP20                                                                                                                              |
| Mounting on DIN Rail                             | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715<br>TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715                                                                             |
| Screw Terminal Type                              | Soldering Pins                                                                                                                                                                             |

## Classifications

|          |                                           |
|----------|-------------------------------------------|
| ETIM 4   | EC000066 - Magnet contactor, AC-switching |
| ETIM 6.0 | EC000010 - Combination of contactors      |
| ETIM 7   | EC000010 - Combination of contactors      |
| ETIM 5.0 | EC000010 - Starter combination            |
| eClass   | 7.0 27371009                              |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Weight         | 0.345 kg |
| Product Net Depth / Length | 51.5 mm  |
| Product Net Width          | 96.5 mm  |
| Product Net Height         | 57.5 mm  |

## Package Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 115 mm        |
| Package Level 1 Height         | 64 mm         |
| Package Level 1 Depth / Length | 280 mm        |
| Package Level 1 EAN            | 4013614416095 |
| Package Level 1 Units          | 5 piece       |

### Package Information

|                              |          |
|------------------------------|----------|
| Package Level 1 Gross Weight | 1.795 kg |
|------------------------------|----------|

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1        |
| Customs Tariff Number  | 85365080 |