

Catalog No. 2TLA020007R6900

Description: JSTD25K TWOHAND CONTROL

UPC No 7350024479690

Home > Machine Safety > Safety Control Devices

Two-hand device with two JSTD1-B Safeballs and one emergency stop button Smile 10 EK. Each Safeball is mounted on a side of a 44x88 extruded aluminum profile designed for two-hand applications. The Smile 10 EK emergency stop button is mounted on top. Safeballs and Smile are pre-wired to a M12-8 male connector. The safeballs have protective flanges.



360°

Representative Image

Descriptors

Category	Safety Control Devices
Type	Two Hand Station

Specifications

Product Class	One and Two Hand Control Devices
Product Main Type	JSTD25
Supply Voltage	24VDC
Degree of Protection	IP65

Classifications

ETIM 4	EC001260 - Two-hand control device
ETIM 5.0	EC001260 - Two-hand control device
ETIM 6.0	EC001260 - Two-hand control device
ETIM 7	EC001260 - Two-hand control device
ETIM 8 (Etim8)	EC001260 - Two-hand control device

Dimensions

Product Net Depth / Length	90.5 mm
Product Net Height	189 mm
Product Net Width	364 mm
Product Net Weight	1.52kg

Safety Information

Performance Level	Up to e
-------------------	---------