



Representative Image

Catalog No. TDT3362R

Description: 60A 3P DBL THR N3R 600V FUSIBLE

UPC No 783164485981

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Double Throw

When it comes to getting the job done right, you can count on safety switches from ABB. ABB offers a wide variety of general duty switches for residential and light commercial purposes, while the extensive line of heavy-duty switches is best suited for commercial and industrial applications. For the toughest industrial environments — such as cement foundries, steel mills and processing plants — dust-tight and stainless steel switches are available. We also offer a variety of double throw switches for emergency generators. No matter the application, we've got you covered with a rugged, reliable and easy-to-install Spec-Setter safety switch. 60A 3P DBL THR N3R 600V FUSIBLE

Descriptors

Category	Double Throw
GO Schedule	SB

Specifications

Voltage	600 AC
Amperage	60 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 3R (Outdoor)
Wire Range (Cu/Al)	14-2 (Cu/Al)
240 Vac, NEC Std, 1-ph	3 hp
240 Vac, NEC Std, 3-ph	7.5 hp
240 Vac, Time Delay, 1-ph	10 hp
240 Vac, Time Delay, 3-ph	15 hp
480 Vac, NEC Std, 1-ph	5 hp
480 Vac, NEC Std, 3-ph	15 hp
480 Vac, Time Delay, 1-ph	20 hp
480 Vac, Time Delay, 3-ph	30 hp
600 Vac, NEC Std, 1-ph	10 hp
600 Vac, NEC Std, 3-ph	15 hp
600 Vac, Time Delay, 1-ph	25 hp
600 Vac, Time Delay, 3-ph	50 hp
125 Vdc	5 hp
250 Vdc	10 hp
GSA Compliance	No

Classifications

cUL Listed	Yes
UL Listed	Yes

by ABB

Dimensions

Height	37.00 in
Width	12.00 in
Weight	44 lb