



Representative Image

## Catalog No. TEY220

**Description:** CIRCUIT BREAKER TWO POLE

**UPC No** 783164180954

**Home > Circuit Breakers > Molded Case Circuit Breakers > Lighting Panel Circuit Breakers**

The TEY is a one-inch wide per pole, compact, "bolt-on" circuit breaker for use on grounded 480Y/277 Vac systems. The bolt-on mounting base accessory makes the TEY suitable for varied applications as a lug-lug breaker. All TEY circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. TEY breakers are available in 1, 2, and 3 pole versions and can be ordered with auxiliary contact and shunt trip accessories. CIRCUIT BREAKER TWO POLE

### Descriptors

|              |                                 |
|--------------|---------------------------------|
| Category     | Lighting Panel Circuit Breakers |
| Product Line | TEY / Q-Line (Bolt-On)          |
| GO Schedule  | EY                              |

### Specifications

|                                 |                                              |
|---------------------------------|----------------------------------------------|
| Trip Style                      | Non-Interchangeable                          |
| Poles                           | 2                                            |
| Amperage                        | 20 A                                         |
| System Voltage                  | 120 Vac<br>120/240 Vac<br>240 Vac<br>277 Vac |
| 120 Vac Interrupting Rating     | 65 KAIC                                      |
| 120/240 Vac Interrupting Rating | 65 KAIC                                      |
| 240 Vac Interrupting Rating     | 65 KAIC                                      |
| 277 Vac Interrupting Rating     | 14 KAIC                                      |
| Trip Function                   | LI                                           |
| Continuous Current Rated        | Standard                                     |
| Suitable for Reverse Feed       | Yes                                          |
| Long Time                       | Fixed                                        |
| Instantaneous                   | Fixed                                        |
| Current Metering                | No                                           |
| Protective Relays               | No                                           |
| Special Markings                | HACR<br>HID                                  |
| Wire Range (Cu/Al)              | 14-8 kcmil / 12-8 kcmil                      |
| GSA Compliance                  | Yes                                          |

### Classifications

|           |         |
|-----------|---------|
| UL File # | E11592  |
| CSA File# | LR57114 |

**by ABB**