



Representative Image

360°

## Alternate Catalog No. DP40C2P-1 Catalog No. 1SBX104200R1200

**Description:** DP CONTR,40A,2P,120/60

**UPC No** 662019754215

**Home > Contactors & Starters > Definite Purpose Contactor**

DP40C2P-1 DP contactor provide outstanding performance in various HVAC, Food service equipment, refrigeration and welding applications and meet all relevant standards, including UL, CSA and IEC. Industry standard mounting plate provides easily accessible mounting holes.

### Descriptors

|          |                            |
|----------|----------------------------|
| Category | Definite Purpose Contactor |
|----------|----------------------------|

### Specifications

|                     |                                          |
|---------------------|------------------------------------------|
| Product Type        | DP Contactor                             |
| Amps Frame          | 40 A                                     |
| Poles               | 2P                                       |
| Coil Voltage        | 120 V                                    |
| Bulk Pack           | Single                                   |
| Special Termination | Standard                                 |
| Order Multiple      | 1                                        |
| Termination         | #14-4 AWG lug with quad quick connectors |

### Classifications

|                        |                    |
|------------------------|--------------------|
| UL / cUL Certification | UL / cUL _ E224401 |
|------------------------|--------------------|

### Dimensions

|        |          |
|--------|----------|
| Length | 2.07 in. |
| Width  | 3.26 in. |
| Height | 2.36 in. |
| Weight | 0.6 lb.  |

### Operating Performance

|                       |                |
|-----------------------|----------------|
| Operating temperature | -40...+65 oC   |
| Insulation Class      | 130 oC Class B |

### Ordering

|                       |          |
|-----------------------|----------|
| Customs Tariff Number | 85365080 |
|-----------------------|----------|

**by ABB**