



Representative Image

## Catalog No. TLM812SCUD1K

**Description:** FLD CNVRTB 125A 8CT 120/240V KIT

**UPC No** 783164302875

**Home > Load Center & Meter Combos > Load Centers**

(Panelboards No. 67) 60 degree/75 degree centigrade Conductor Rating Suitable for use as service entrance equipment when Installed in accordance with the National Electrical Code 22kAIC RMS symmetrical, Except Where Noted 6-42 circuit devices UL Listed for bottom mounted lugs by installing complete unit (box, interior and front) upside down For a listing of CSA Listed load centers, visit [www.geeectrical.com](http://www.geeectrical.com) Amperage 125 A

### Descriptors

|             |                    |
|-------------|--------------------|
| Category    | Load Centers       |
| GO Schedule | RD                 |
| Grouping    | Single Phase - USA |

### Specifications

|                              |                              |
|------------------------------|------------------------------|
| 1" Space                     | 8                            |
| 1/2" Space                   | 16                           |
| Amperage                     | 125 A                        |
| Device type                  | Convertible                  |
| Door                         | Yes                          |
| Enclosure                    | Indoor                       |
| Feed                         | Either                       |
| Input/Output Voltage         | 120/240V ac                  |
| Interrupting Capacity Rating | 65                           |
| Load Center Type             | Standard                     |
| Phase                        | 1 Phase                      |
| Service & Voltage            | 1 Phase, 3 Wire, 120/240V ac |
| Wires                        | 3 Wire                       |

### Classifications

|                |    |
|----------------|----|
| UL/CUL Listing | UL |
|----------------|----|